



APPLICATION INFORMATION FOR IKO AQUABARRIER PRIMER II

IKO AquaBarrier Primer II is a two-part, solvent-free, quick-setting, primer/adhesive for use with AquaBarrier AVB and FP self-adhesive membranes in conjunction with a multitude of substrates such as wood, EPS, gypsum board, masonry, concrete, and metal. May be applied to (green) concrete only 24 hours after pouring.

All surfaces should be dry and free from moisture, oil, grease, dirt and loose materials. Metal surfaces must have all rust scales removed. **Add Part B to the half filled container of Part A and power-mix until the colour is even (black). Do not mix more primer than may be applied in one hour.** IKO AquaBarrier Primer II should be applied with a short pile roller (5mm) – only a thin coat is needed. The recommended spread rate is approximately 20m² per 3.78 L (200 ft² per gal). May be applied from -20°C to 40°C. Through cure time will vary depending on temperature. Membrane may be installed 30-45 minutes after application of primer, or up to 48 hours after primer application. If left for more than 24 hours, touch surface to make sure there is still suitable tack, as rain or dust could reduce surface tack, in which case another application of primer will be required. Clean tools immediately after use, as this product cannot be washed once cured.

Store indoors protected from temperature extremes.

Do not thin with water or solvent.

Tools and equipment may be cleaned immediately after use (before cure) with mineral spirits. Take necessary precautions when handling combustible materials.

Do not inhale vapours. Do not take internally. Use only in well ventilated areas. Wear eye and face protection. Protect hands with impervious rubber gloves. For additional health and safety information. Read the MSDS carefully before using the product.

For additional information on any of IKO's products or application requirements, visit us on the web at www.iko.com (North America), or contact us in Canada/United States at 1-800-361-5836 (press "1" for English and then "2" for our Technical Support Department).

