



# InnoviFlash<sup>TM</sup> 2-Way Breather Vent

## System Compatibility

InnoviFlash 2-Way Breather Vents are intended for use with IKO InnoviTPO Roofing Systems and are approved for use with an appropriate IKO Diamond Shield Limited Warranty. Building owners, specifiers, roof consultants and roofing contractors are invited to review the IKO InnoviTPO System Specifications at [www.iko.com/comm](http://www.iko.com/comm) for further information on including this product as part of a complete IKO roofing system.

## Pre-attached Flange Makes Heat Welding Efficient

InnoviFlash 2-Way Breather Vents make heat welding fast and easy, resulting in labor savings during installation. The vents are also designed with vandal proof caps.

## Vents Work in Conjunction With 1-Way Vents

InnoviFlash 2-Way Breather Vents help reduce moisture by allowing air movement within the roofing assembly together with 1-way vents, which allow trapped air pressure to escape.

**Stock #:** 6212060, 6212170, 6212173

**Size:** 4 in. (101.6 mm)

**Height:** 9 in. (229 mm)

**Diameter:** 4.25 in. (108 mm)

**Flange:** 7.5 in. (190.5 mm)

**Membrane Patch:** 12 in. (305 mm)

**Quantity per box:** 12

**Weight per box:** 7 lbs. (3.1 kg)

**Colors:** White, Grey, Tan

**Note:** Call IKO for grey or tan recommendations.

All reported values are nominal.

- Breather vent meets 8-inch (203.2 mm) minimum height specification.
- Flange is 60 mil reinforced TPO.
- Easier welding during installation.
- Aids air movement within the roofing assembly.

The information on this sheet is based on data supplied by the manufacturer to IKO and believed to be true and accurate. The information is offered solely for the user's consideration, investigation and verification. Nothing contained herein constitutes or represents a warranty or guarantee for which the manufacturer or the distributor can be held legally responsible.