



## InnoviFlash<sup>TM</sup> TPO Joint Cover

**Stock #:** 6203060, 6203170, 6203173

**Material Type:** Non-Reinforced  
TPO Membrane

**Thickness:** .060 in. (60 mils) (1.52 mm)

**Diameter:** 4.5 in. (114.3 mm)

**Colors:** White, Grey, Tan

**Quantity per Box:** 100

**Weight per Box:** 3.5 lbs. (1.5 kg)

All reported values are nominal.

### System Compatibility

InnoviFlash TPO Joint Covers are intended for use with IKO InnoviTPO Roofing Systems and are approved for use with an appropriate IKO Diamond Shield Limited Warranty. Building owners, specifiers, roof consultants and roofing contractors are invited to review the IKO InnoviTPO System Specifications at [www.iko.com/comm](http://www.iko.com/comm) for further information on including this product as part of a complete IKO roofing system.

### Factory Cut 4.5 in. Diameter Assures Uniformity

InnoviFlash TPO Joint Covers are essential to preventing leaks at intersections of three or more membrane layers. They provide for reliable welds and enhance seals in the roof area.

### Installed Cost is Lower than Field Fabricated Alternatives

InnoviFlash TPO Joint Covers save a significant amount of labor compared to field fabrication with a better fit. Contractors appreciate the efficiency of IKO InnoviFlash TPO Joint Covers on the job.

- Used to seal intersections of membranes.
- Uniformity is superior to hand cut patches.
- Assures reliable welds.

## InnoviFlash<sup>TM</sup> TPO Joint Cover

### Installation

1. Keep TPO Joint Covers in their original bag until installation.
2. Center the InnoviFlash TPO Joint Cover over the intersection of the membrane sheets.
3. Heat weld the TPO Joint Covers beginning from the middle and progressing out, until the entire cover is fully welded.
4. Carefully roll in the cover using a silicone roller, pressing the cover into the membrane to create a complete seal, during heat-welding.

The information on this sheet is based on data supplied by the manufacturer to IKO and believed to be true and accurate. The information is offered solely for the user's consideration, investigation and verification. Nothing contained herein constitutes or represents a warranty or guarantee for which the manufacturer or the distributor can be held legally responsible.