



InnoviFlashTM TPO Scupper

System Compatibility

InnoviFlash TPO Scupper is intended for use with IKO InnoviTPO Roofing Systems and is approved for use with an appropriate IKO Diamond Shield Limited Warranty. Building owners, specifiers, roof consultants and roofing contractors are invited to review the IKO InnoviTPO System Specifications at www.iko.com/comm for further information on including this product as part of a complete IKO roofing system.

Prefabricated for Efficient Installation

InnoviFlash TPO Scupper does not require assembly on-site, so installation is easy. With no complicated assembly, only a finishing weld is required. It is designed to be simple and aesthetic.

Installation

1. Insert appropriately sized scupper into hole in perimeter wall.
2. Lift membrane flange and fasten to deck and wall through coated metal flange.
3. Heat weld membrane flange to field and wall membrane.
4. Apply InnoviSealTM TPO Cut Edge Sealant around edge of flange.
5. See the relevant IKO Commercial Details for additional flashing requirements.

Stock #: 6223060, 6223170, 6224060, 6224170, 6225060, 6225170

Thickness: .060 in. (60 mils) (1.52 mm)

| Item # | Color | Opening Height | Opening Width | Depth |
|---------|-------|----------------|---------------|-------|
| 6223060 | White | 6" | 6" | 14" |
| 6223170 | Grey | 6" | 6" | 14" |
| 6224060 | White | 6" | 9" | 14" |
| 6224170 | Grey | 6" | 9" | 14" |
| 6225060 | White | 6" | 12" | 14" |
| 6225170 | Grey | 6" | 12" | 14" |

All reported values are nominal.

- Preassembled for easy installation.
- Provides an aesthetic visual finish.
- One piece requires a finishing weld only.

The information on this sheet is based on data supplied by the manufacturer to IKO and believed to be true and accurate. The information is offered solely for the user's consideration, investigation and verification. Nothing contained herein constitutes or represents a warranty or guarantee for which the manufacturer or the distributor can be held legally responsible.