

# **InnoviFlash**™ TPO Unsupported Flashing

**Stock #:** 6226060, 6226170, 6226173

Material type:

Non-reinforced TPO membrane

Thickness: 60 mil (0.060 in.) (1.52 mm)

Sheet Size:

24 in. x 50 ft. (610 mm x 15.24 m)

Coverage: 100 ft.2 (9 m2)

**Weight:** 36 lbs. (16.3 kg)

Packaging: 1 roll per bag

Colors: White, Grey, Tan

All reported values are nominal.

- Excellent weldability.
- Field fabrication for a variety of uses.
- Exceptionally flexible.

## **System Compatibility**

InnoviFlash TPO Unsupported Flashing are intended for use with IKO InnoviTPO Roofing Systems and are approved for use with an appropriate IKO Diamond Shield Limitied Warranty. Building owners, specifiers, roof consultants and roofing contractors are invited to review the IKO InnoviTPO System Specifications at www.iko.com/comm for further information on including this product as part of a complete IKO roofing system.

#### Ideal for Field Fabrication

InnoviFlash TPO Unsupported Flashings fit many different applications on the roof and make ideal flashings for pipes, curbs, sealant pockets, scuppers, vents, drains and other details.

#### **Excellent Weldability and Flexibility**

InnoviFlash TPO Unsupported Flashings are non-reinforced, so they easily conform to a variety of field conditions.





# **InnoviFlash**<sup>™</sup> TPO Unsupported Flashing

## Installation

- 1. Substrates must be clean, dry, smooth and free of sharp edges, fins, loose or foreign materials, oil, grease and other materials that may damage the InnoviFlash TPO Unsupported Flashing.
- 2. All surface voids greater than a 1/4-inch (6.3 mm) wide must be filled with acceptable fill material.
- 3. Install InnoviFlash TPO Unsupported Flashing material with appropriate heat-welding equipment in accordance with current IKO specifications, details and technical information.

The information on this sheet is based on data supplied by the manufacturer to IKO and believed to be true and accurate. The information is offered solely for the user's consideration, investigation and verification. Nothing contained herein constitutes or represents a warranty or guarantee for which the manufacturer or the distributor can be held legally responsible.

