



InnoviFastTM 2 in. AP Seam Plates

System Compatibility

InnoviFast 2 in. AP Seam Plates are intended for use with IKO InnoviTPO Roofing Systems and are approved for use with an appropriate IKO Diamond Shield Limited Warranty. Building owners, specifiers, roof consultants and roofing contractors are invited to review the IKO InnoviTPO System Specifications at www.iko.com/comm for further information on including this product as part of a complete IKO roofing system.

Galvalume[®] Seam Plate Provides Increased Protection Against Corrosion

InnoviFast 2 in. AP Seam Plates are protected with a high-performance alloy of aluminum and zinc. Zinc bonds with the steel to create a barrier to moisture, and aluminum resists corrosion to provide robust protection.

Excellent Attachment for TPO Membranes and Cover Boards

The engineered barbed design provides increased wind uplift performance when used for roof system attachment to steel and wood roof decks. The flat-bottom design is ideal for use on rigid surfaces. InnoviFast 2 in. AP Seam Plates are intended for use with InnoviFast AP Fasteners, concrete deck fasteners, and other approved IKO fastening products.

Galvalume[®] is a registered trademark of BIEC International, Inc.

Tectum[®] is a registered trademark of Armstrong World Industries.

The information on this sheet is based on data supplied by the manufacturer to IKO and believed to be true and accurate. The information is offered solely for the user's consideration, investigation and verification. Nothing contained herein constitutes or represents a warranty or guarantee for which the manufacturer or the distributor can be held legally responsible. Galvalume[®] is a registered trademark of BIEC International, Inc.

Stock #: 6300001
OD: 2 in. (50.8 mm) round
Thickness: 0.032 in. (0.8 mm)
Finish: AZ55 Galvalume[®]
Pail Weight: 41 lbs. (18.5 kg)
Quantity/Pail: 1,000

All reported values are nominal.

- For membrane and cover board attachment.
- Engineered barb design provides increased wind uplift performance.
- 22 ga. 55% aluminum-zinc alloy coated steel.

