



InnoviFastTM Insulation Plate

Stock #: 6300079
OD: 3 in. (76.2 mm)
Thickness: 0.019 in. (0.4 mm)
Finish: AZ50 Galvalume®
Pail Weight: 41 lb. (18.5 kg)
Pail Quantity: 1,000

All reported values are nominal.

- Insulation and cover board attachment.
- Designed for steel and wood roof decks.
- 26 ga. 55% aluminum-zinc alloy coated steel.

System Compatibility

InnoviFast Insulation Plates are intended for use with IKO Innovo TPO Roofing Systems and are approved for use with an appropriate IKO Diamond Shield Limited Warranty. Building owners, specifiers, roof consultants and roofing contractors are invited to review the Innovo TPO System Specifications at www.iko.com/comm for further information on including this product as part of a complete IKO roofing system.

Galvalume® Stress Plate Provides Increased Protection Against Corrosion

InnoviFast Insulation Plates are protected with a high-performance alloy of aluminum and zinc. Zinc bonds with the steel to create a barrier to moisture, and aluminum resists corrosion to provide robust protection.

Excellent Attachment for Roof Insulation and Cover Boards

InnoviFast Insulation Plates are designed for roof system attachment to steel and wood roof decks. The flat-bottom design is ideal for use on rigid board surfaces. These plates may be used with most IKO InnoviFast fasteners, including:

- InnoviFast Insulation Fasteners (#12).
- InnoviFast All Purpose (AP) Fasteners. (#14).
- InnoviFast Heavy Duty (HD) Fasteners (#15).
- InnoviFast Concrete Drive Pins.

Galvalume® is a registered trademark of BIEC International, Inc.
Tectum® is a registered trademark of Armstrong World Industries.

The information on this sheet is based on data supplied by the manufacturer to IKO and believed to be true and accurate. The information is offered solely for the user's consideration, investigation and verification. Nothing contained herein constitutes or represents a warranty or guarantee for which the manufacturer or the distributor can be held legally responsible.

