Type IV Glass Ply Sheet

ASPHALT SATURATED FIBERGLASS MAT

STOCK# **0640092**

QUANTITY PER PALLET: **24**

PALLET SIZE: **112 cm x 112 cm**

(44 in. x 44 in.)

LENGTH: **50.2 m (164.6 ft.)**

WIDTH: **1000 mm (39 3/8 in.)**

AREA: **50 m² (540 ft.²)**

Note: All reported values are nominal.

- MINIMIZES MOISTURE
- MULTI-USE

Specially designed to alleviate moisture build up and easy to install, let IKO Type IV Glass Ply Sheet go to work for your next commercial roofing project.

Type IV Glass Ply Sheet

ASPHALT SATURATED FIBERGLASS MAT

Asphalt Permeated
IKO Type IV Glass Ply Sheet is composed of a high-strength, inorganic mat of non-woven glass fibers, which has been thoroughly permeated with premium asphalt.

Minimizes Moisture Build Up
Offers greater moisture resistance, enabling a four-ply application to provide substantially greater performance characteristics than a conventional four-ply organic felt built-up roofing system.

Non-Stick
This product's surface is sprayed with a water-based soap solution to prevent sticking in the roll.

Superior Strength
IKO Type IV Glass Ply Sheets provide superior "breaking strength" characteristics in both longitudinal and transverse directions.

Type IV
Glass Ply Sheet

ASPHALT SATURATED FIBERGLASS MAT

This sheet complies with all CSA A123.17 and ASTM D2178 Type IV specifications.

Please contact your IKO Technical Representative for specific slope requirements.

CHARACTERISTICS	UNITS	NOMINAL VALUE	TEST METHOD	STANDARD LIMITS
Cold Flex:	° C (° F)	✓	ASTM D146	MIN: 10 (50)
Tensile Strength MD: XD:	kN/m (lbf/in.)	✓ ✓	ASTM D146	MIN: 7.7 (44) MIN: 7.7 (44)