

# Protectoboard™ 3 mm (1/8")

COMMERCIAL  
ROOF COVER BOARD

STOCK# 0910021, 0910023,

0910034, 0910036, 0910037

BOARDS PER PALLET:

122 cm x 120 cm (4 ft x 47-1/4 in) - 150

122 cm x 61 cm (4 ft x 2 ft) - 300

122 cm x 82 cm (4 ft x 32-1/8 in) - 225

122 cm x 14 cm (4 ft x 16 in) - 250

127 cm x 121 cm (50 in x 47-1/4 in) - 150

LENGTH: 0910021 - 120 cm (47-1/4 in)

0910023 - 61 cm (2 ft);

0910034 - 82 cm (32-1/8 in),

0910036 - 14 cm (16 in);

0910037 - 121 cm (47-1/4 in)

WIDTH: 0910021, 0910023, 0910034,

0910036, -122 cm (4 ft)

0910037 - 127 cm (50 in)

THICKNESS: 3 mm (1/8 in)

WEIGHT: 122 cm x 120 cm

(4 ft x 47-1/4 in) - 5.8 kg (12.8 lb)

122 cm x 61 cm (4 ft x 2 ft) - 3.2 kg (7 lb)

122 cm x 82 cm (4 ft x 32-1/8 in)

- 4.2 kg (9.3 lb)

122 cm x 14 cm (4 ft x 16 in)

- 2.1 kg (4.6 lb)

127 cm x 120 cm (50 in X 47-1/4 in)

- 5.9 kg (13 lb)

Note: All reported values are nominal.



# IKO® COMMERCIAL



Used in either roofing or waterproofing applications, let IKO Protectoboard Cover Board go to work for your next commercial construction project.

## Protectoboard™ 3 mm (1/8")

COMMERCIAL ROOF COVER BOARD

### High Strength

Protectoboard 3 mm (1/8") is composed of a mineral-fortified asphaltic core between two layers of high-strength reinforcing glass fiber mat.

### Other Uses

Protectoboard also can be applied as a protection board in the waterproofing of bridge and podium decks, vertical walls and parking garages.

### Versatile Roofing Applications

Protectoboard can be used as an overlay board in any conventional roof system, either in an inverted roofing assembly or as the new substrate for modified bitumen or four-ply asphalt and felt re-roof application.



- OUTSTANDING STRENGTH
- MOISTURE RESISTANT

# Protectoboard™ 3 mm (1/8")

COMMERCIAL  
ROOF COVER BOARD



# COMMERCIAL



IKO building products are responsibly designed and produced with consideration for sustainability and the environment, incorporating quality recycled components where practical, manufactured in facilities that comply with environmental standards.

ISO 9001 - 2008 REGISTERED FACILITY

Please contact your *IKO* Technical Representative for specific slope requirements.

CHARACTERISTICS	UNITS	MEETS/ EXCEEDS	TEST METHOD	STANDARD LIMITS
Thickness:	mm (in)	3 (1/8)	—	± 10%
Moisture Content:	%	✓	ASTM D146	MAX: 5
Moisture Absorption:	%	✓	DSM #9.90.60	MAX: 5
Dimensional Stability:	%	✓	ASTM D1204	MAX: 1.0

The information on this product information sheet is based upon data considered to be true and accurate, based on laboratory tests and production measurements, and is offered solely for the user's consideration, investigation and verification. Nothing contained herein is representative of a warranty or guarantee for which the manufacturer can be held legally responsible. The manufacturer does not assume any responsibility for any misrepresentation or assumptions the reader may formulate.

