



InnoviFlashTM TPO Drain Flashing

Stock #: 6200007-6200010

Thickness: .060 in. (60 Mils) (1.52 mm)

Flange Colors: White, Grey, Tan

Flashing Dimensions:
23 1/2 in. X 23 1/2 in. (596.9 mm x 596.9 mm)

Drain Depth: 12 1/2 in. (317.5 mm)

Drain Diameter: 2 in. (50.8 mm),
3 in. (76.2 mm), 4 in. (101.6 mm), 5 in. (127 mm),
6 in. (152.4 mm)

Pipe Diameter: 1 1/2 in. (38.1 mm), 2 1/2 in.
(63.5 mm), 3 1/2 in. (88.9 mm),
4 1/2 in. (114.3 mm) and 5 1/2 in. (139.7 mm).

Quantity: 1 drain/box

All reported values are nominal.

- Preassembled for easy installation.
- One piece with .64 gauge aluminum.

System Compatibility

InnoviFlash TPO Drain Flashing is intended for use with IKO InnoviTPO Roofing Systems and is approved for use with an appropriate IKO Diamond Shield Limited Warranty. Building owners, specifiers, roof consultants and roofing contractors are invited to review the IKO InnoviTPO System Specifications at www.iko.com/comm for further information on including this product as part of a complete IKO roofing system.

Innovative Accessory for Professional Commercial Roof Installation

InnoviFlash TPO Drain Flashing is made from 60-mil IKO Innovi TPO, with TPO coated metal and a metal downspout. The downspout is designed to be inserted into existing external drain pipes (soffit drains) for rainwater runoff. For internal drains, use a mechanically attached drain insert with basket (by others).

Prefabricated for Efficient Installation

InnoviFlash TPO Drain Flashing does not require assembly on-site, so installation is easy. The aluminum component is robust and durable. It is designed to be simple and aesthetic.

InnoviFlashTM TPO Drain Flashing

Installation

1. Insert appropriately sized InnoviFlash TPO Drain Flashing downspout into existing drain.
2. Lift membrane flange and fasten to deck through coated metal flange.
3. Heat weld membrane flange to field membrane.
4. Apply InnovisealTM TPO Edge Sealant to all cut edges in field membrane.

The information on this sheet is based on data supplied by the manufacturer to IKO and believed to be true and accurate. The information is offered solely for the user's consideration, investigation and verification. Nothing contained herein constitutes or represents a warranty or guarantee for which the manufacturer or the distributor can be held legally responsible.