



InnoviFastTM Auger Insulation Plate

System Compatibility

InnoviFast Auger Insulation Plates are intended for use with all IKO InnoviTPO Roofing Systems and are approved for use with an appropriate IKO Diamond Shield Limited Warranty. Building owners, specifiers, roof consultants and roofing contractors are invited to review the IKO InnoviTPO System Specifications at www.iko.com/comm for further information on including this product as part of a complete IKO roofing system.

Galvalume[®] Stress Plate Provides Increased Protection Against Corrosion

InnoviFast Auger Insulation Plates are protected with a high-performance alloy of aluminum and zinc. Zinc bonds with the steel to create a barrier to moisture and aluminum resists corrosion to provide for robust protection.

For Use with Lightweight Concrete, Gypsum and Tectum Decks

InnoviFast Auger Insulation Plates are designed for use with InnoviFast Polymer Augers. They are for use with lightweight concrete, gypsum or tectum roof decks. The barb design allows for high wind uplift ratings.

Galvalume[®] is a registered trademark of BIEC International, Inc.
Tectum[®] is a registered trademark of Armstrong World Industries.

The information on this sheet is based on data supplied by the manufacturer to IKO and believed to be true and accurate. The information is offered solely for the user's consideration, investigation and verification. Nothing contained herein constitutes or represents a warranty or guarantee for which the manufacturer or the distributor can be held legally responsible.

Stock #: 6300056
OD: 3 in. (76.2 mm) Round
Width: 0.017 in. (0.43 mm)
Finish: AZ55 galvalume[®]
Pail weight: 18 lbs. (8.1 kg)
Pail quantity: 500

All reported values are nominal.

- Insulation plate.
- For lightweight concrete, gypsum and tectum[®] decks.
- 26 ga. 55% aluminum–45% zinc alloy coated steel.
- High wind uplift rating.