



InnoviFastTM Stainless Steel Fasteners

Stock #: 6300084-6300093

Thread Lengths:

Range from full, 2 7/8-in. (73 mm) to 3 7/8-in. (98.4 mm)

Fastener Length in. (mm):	Pail Weight lb. (kg):	Pail Quantity:
1 1/2 (38.1)	14 (6.3)	1,000
2 (50.8)	18 (8.1)	1,000
3 (76.2)	25 (11.3)	1,000
4 (101.6)	32 (14.5)	1,000
5 (127)	39 (17.6)	1,000
6 (152.4)	46 (20.8)	1,000
7 (177.8)	27 (12.2)	500
8 (203.2)	30 (13.6)	500
10 (254)	39 (17.6)	250
12 (304.8)	48 (21.7)	250

All reported values are nominal.

- 410 stainless steel provides enhanced resistance to corrosion.
- May be used for both insulation and membrane attachment.
- #14 fastener, ideal for steel or wood decks.

System Compatibility

InnoviFast Stainless Steel Fasteners are intended for use with IKO InnoviTPO Roofing Systems and are approved for use with an appropriate IKO Diamond Shield Limited Warranty. Building owners, specifiers, roof consultants and roofing contractors are invited to review the IKO InnoviTPO System Specifications at www.iko.com/comm for further information on including this product as part of a complete IKO roofing system.

Features and Benefits

- InnoviFast TPO Stainless Steel Fasteners resist corrosion in mild to light industrial environments.
- 13 threads per inch (26 mm) provide for easy installation in either steel or wood roof decks.
- The low-profile truss head can be used for attachment in installations where the head height is critical.
- A #3 Phillips bit is included in each standard pail package.

InnoviFastTM Stainless Steel Fasteners

Installation

1. Tools: Use a 2,000–2,500-rpm screw gun with a hardened #3 Phillips bit (included).
2. Minimum penetrations:
 - Steel decks: 3/4 inch (19 mm) through deck.
 - Wood decks: 1 inch (26 mm) into or through deck.
3. Note: These fasteners are not recommended for use in heavy industrial, marine or enclosed swimming pool environments.
4. These fasteners can be installed with InnoviFast batten bars, insulation plates or membrane seam plates.

Storage

Store in original carton in a cool, dry location.

The information on this sheet is based on data supplied by the manufacturer to IKO and believed to be true and accurate. The information is offered solely for the user's consideration, investigation and verification. Nothing contained herein constitutes or represents a warranty or guarantee for which the manufacturer or the distributor can be held legally responsible.