

# IKO Mod-Bit Primer

MOD-BIT PRIMER



# IKO<sup>®</sup> COMMERCIAL



STOCK# 7870010

SIZE: 18.93L (5 US gal)

PAIS PER PALLET: 36

PALLET SIZE: 122 cm x 102 cm  
(48 in x 40 in)

COVERAGE\*: 4 m<sup>2</sup>/L to 7 m<sup>2</sup>/L  
(165 ft<sup>2</sup>/gal to 250 ft<sup>2</sup>/gal)

DRYING TIME: 60 minutes

Note: All reported values are nominal.

## IKO Mod-Bit Primer

MOD-BIT PRIMER

### Solvent Based

IKO Mod-Bit Primer is solvent-based and intended to prepare roofing and wall surfaces prior to applying heat-welded membranes.

### Easy Application

IKO Mod-Bit Primer can be applied with a brush, roller or sprayer.

### Quick Drying

IKO Mod-Bit Primer is formulated with a rubber modified bitumen and fast-evaporating solvents for quick drying.

### Suitable for Multiple Substrates

The modified bitumen enhances membrane adhesion to a variety of substrates such as gypsum, masonry, metal, concrete or CMU and improves membrane performance over a wide range of temperatures and conditions.\*

Quick drying and easy to apply, let IKO Mod-Bit Primer go to work for your next project.

- EASY APPLICATION
- QUICK DRYING

\*Depending on porosity and texture of surface

# IKO Mod-Bit Primer

MOD-BIT PRIMER



# IKO<sup>®</sup> COMMERCIAL

**Application considerations:** Surfaces to be primed must be dry and clean. Primer must be thoroughly dry before attempting to apply the membrane. Do not attempt to accelerate the drying time of the primer by heating with a torch! Always use caution when handling flammable materials.

All local health and safety rules and precautions should be followed when working with IKO products. See Also Material Safety Data Sheet MSDS #1255.

Good building practices include ensuring the application surface is adequately prepared for the adhesion of the product prior to installing it. For further details please refer to the “IKO Installation Guidelines”.

Please contact your IKO Technical Representative for specific slope requirements.



| CHARACTERISTICS                                     | UNITS                                    | NOMINAL VALUE       |
|---|--|---------------------|
| Non-Volatile (By Weight):                           | %  | 35                  |
| Flash Point (TCC):                                  | °C (°F)                                  | > -18 (-4)          |
| Specific Gravity:                                   | Kg/L                                     | 0.85                |
| Viscosity @ 25°C                                    | cps                                      | 50 - 100            |
| Volatile Organic Compounds (VOC):                   | g/L                                      | 545                 |
| Minimum Application Temperature:                    | °C (°F)                                  | > -12 (10.4)        |
| Coverage  | m <sup>2</sup> /L (ft <sup>2</sup> /gal) | 4 to 7 (165 to 250) |
| Drying Time (@ 50% R.H., 25°C, and Dry Substrate)** | Hours                                    | 1                   |

The information on this product information sheet is based upon data considered to be true and accurate, based on laboratory tests and production measurements, and is offered solely for the user's consideration, investigation and verification. Nothing contained herein is representative of a warranty or guarantee for which the manufacturer can be held legally responsible. The manufacturer does not assume any responsibility for any misrepresentation or assumptions the reader may formulate.