

IKO Standard Asphalt Primer

ROOFING PRIMER



IKO[®] COMMERCIAL



STOCK# 7870013

SIZE: 18.9 L (5 gal)

PAIS PER PALLET: 36

COLOUR: Black

COVERAGE*: 1.5-2.4 m²/L (60-100 ft²/Gal)

DRYING TIME: 2-4 hours

* Depending on porosity and texture of surface.

IKO Standard Asphalt Primer

ROOFING PRIMER

Multiple Asphalt Applications

IKO Standard Asphalt Primer is an asphalt-based primer for use prior to the application of hot asphalt, fibrated asphalt coatings, asphalt emulsions, or asphalt adhesives.

Dries Fast

It is used as a single coat when fast drying is needed to accelerate the roof system installation process.

Multi-Purpose

May be used to prime and/or seal gypsum, masonry, metal, wood, concrete, asphalt and other similar substrates.

Versatile and fast-drying, let IKO Standard Asphalt Primer go to work for your next commercial roofing project.

- VERSATILE
- ONE COAT APPLICATION

IKO Standard Asphalt Primer

ROOFING PRIMER



COMMERCIAL



IKO Standard Asphalt Primer meets the requirements of CGSB 37-GP-9Ma and ASTM D41.

Please contact your *IKO* Technical Representative for specific slope requirements.

CHARACTERISTICS	UNITS	NOMINAL VALUE
Total Solid by Weight:	%	50 min.
Flash Point (TCC):	°C	> 45
Specific Gravity:	kg/L	0.89 – 0.91

See also Material Safety Data Sheet - MSDS # 1258. Not intended for interior applications. Not for use as a primer for peel and stick membranes. The information on this product information sheet is based upon data considered to be true and accurate, based on laboratory tests and production measurements, and is offered solely for the user's consideration, investigation and verification. Nothing contained herein is representative of a warranty or guarantee for which the manufacturer can be held legally responsible. The manufacturer does not assume any responsibility for any misrepresentation or assumptions the reader may formulate.

