

## Dynamic Wind Uplift Resistance CSA A123.21-2014 – Summary Document

Document No.: 19-06-B0127-AARS005-A  
Document Date: October 11, 2019

Reference Documentation:

CSA A123.21-2014 Report No: 16-06-M0284  
Supplementary Report No.: 19-06-B0042-M

<b>Manufacturer:</b>	IKO Industries Ltd.		<b>IKO System Identification:</b>
	40 Hansen Road South		
	Brampton, Ontario, Canada		
	L6W 3H4		<b>AARS005</b>

### SECTION 1.0: Roof System Summary:

<b>"IKO MOD-BIT ADHERED OVER THERMAL BARRIER" – Adhesive Adhered Roofing System</b>	
Roof Membrane – Cap Sheet:	IKO Torchflex TP-180-Cap
Roof Membrane – Base Sheet	IKO Torchflex TF-95-FF-Base
Cover Board:	IKO Protectoboard
Insulation:	IKO IKOTerm
Insulation:	IKO IKOTerm
Vapour Retarder:	IKO Armourbond Flash Sand
Thermal Barrier:	GP 12.7 mm (1/2") DensDeck Prime®
Deck:	Steel Deck, 22 ga, RD938, 230 MPa (33.4 ksi)

### SECTION 2.0: System Dynamic Wind Uplift Resistance (DUR) Testing Details:

<b>Test Date</b>	<b>Dynamic Wind Uplift Resistance (DUR) of tested specimen kPa (psf)</b>	<b>Dynamic Wind Uplift Resistance (DUR)* Rating (with 1.5X safety factor) kPa (psf)</b>
November 26, 2016	5.7 (120)	3.8 (80)

**Dynamic Wind Uplift Resistance Rating (DUR): 3.8 kPa (80 psf)**

**SECTION 3.0: Tested Product and Substitutable Products:**

Roof Membrane (Cap Sheet)			
Tested Product	IKO Torchflex TP-180-Cap		
Product Size	Roll Width: 1 m (39.6"), roll Length 8 m (26')		
Attachment Method	Heat Welded		
Substitutable Product(s)			
Manufacturer	Product Identification		
IKO Industries Ltd.	Torchflex TP-HD-Cap	Torchflex TP-250-Cap	Torchflex TP-250-Cap (5 mm)
	PrevENT TP-250-Cap	PrevENT TP-HD-Cap	PrevENT Premium TP-250-Cap
	ArmourCool Granular TP-HD	PrevENT ArmourCool Granular TP	PrevENT ArmourCool HD Cap
	Carrara ArmourCool HD		
IKO Industries Ltd.	Modiflex MP-180-cap	Modiflex MP-250-cap	Modiflex MP-HD-cap
	PrevENT MP-250-cap	PrevENT MP-HD-cap	

Roof Membrane (Base Sheet)			
Tested Product	IKO Torchflex TF-95-FF-Base		
Product Size	Roll Width: 1 m (39.6"), roll Length 15 m (49')		
Attachment Method	Heat Welded		
Substitutable Product(s)			
Manufacturer	Product Identification		
IKO Industries Ltd.	Torchflex TF-95-SF-Base	Torchflex TP-180-FF-Base	Torchflex TP-180-SF-Base
	Torchflex HD-FF-Base		
IKO Industries Ltd.	Modiflex MF-95-FS-Base	Modiflex MF-95-SS-Base	Modiflex MP-180-FS-Base
	Modiflex MP-180-SS-Base	Modiflex MP-180-FS-Base 3mm	Modiflex MP-HD-FS-Base
	Modiflex MP-HD-SS-Base		

Cover Board	
Tested Product	IKO Protectoboard
Product Size	3 x 1220 x 1524 mm (1/8" x 4' x 5')
Attachment Method	Ribbon adhered with IKO Millennium adhesive
Fastening Rate	305 mm (12") o.c.
Substitutable Product(s)	
Manufacturer	Product Identification
IKO Industries Ltd.	Protectobase 180

Insulation (Top Layer)			
Tested Product	IKO IKOTerm		
Product Size	51 x 1220 x 1220 mm (2" x 4' x 4')		
Attachment Method	Ribbon adhered with IKO Millennium adhesive		
Fastening Rate	305 mm (12") o.c.		
Substitutable Product(s)			
Manufacturer	Product Identification		
IKO Industries Ltd.	IKOTerm III	IKOTerm 25 psi	IKOTerm III 25 psi
	IKOTerm Tapered	IKOTerm III Tapered	IKOTerm 25 psi Tapered

Insulation (Bottom Layer)			
Tested Product	IKO IKOTerm		
Product Size	51 x 1220 x 1220 mm (2" x 4' x 4')		
Attachment Method	Ribbon adhered with IKO Millennium adhesive		
Fastening Rate	305 mm (12") o.c.		
Substitutable Product(s)			
Manufacturer	Product Identification		
IKO Industries Ltd.	IKOTerm III	IKOTerm 25 psi	IKOTerm III 25 psi
	IKOTerm Tapered	IKOTerm III Tapered	IKOTerm 25 psi Tapered

Vapour Retarder	
Tested Product	IKO Armourbond Flash Sand
Product Size	Roll Width: 1 m (39.6"), roll Length 15 m (49')
Attachment Method	Self-adhered to substrate primed with IKO S.A.M. adhesive
Fastening Rate	n/a
Substitutable Product(s)	
Manufacturer	Product Identification
IKO Industries Ltd.	MVP Sand   AmourGard Ice and Water Protector Commercial

Thermal Barrier	
Tested Product	GP DensDeck Prime®
Product Size	12.7 x 1220 x 2440 mm (1/2" x 4' x 8')
Attachment Method	Ribbon adhered with IKO Millennium adhesive
Fastening Rate	305 mm (12") o.c.
Substitutable Product(s)	
Manufacturer	Product Identification
n/a	n/a

Assembly Adhesive Securement	
Tested Product	IKO Millennium adhesive – ribbon adhered
Fastening Rate	305 mm (12") o.c.
Substitutional Product(s)	
Manufacturer	Product Identification
n/a	n/a

*Note: This is not a comprehensive report but a summary of the performance results produced for the roof assembly documented herein tested in accordance to CSA A123.21-2014. Please refer to the reference documents stated on page 1, or consult the manufacturer, for detailed information pertaining to the test specimen configuration and construction.*

**Reported by:**



Allan Lawrence, Ext. 11212  
Supervisor, Building Systems  
Industrials Division

**Authorized by:**



Jordan Church, B. Tech., Ext. 11546  
Ops. / Tech. Manager, Bldg. Science & Fire Testing  
Industrials Division

**Accreditation:** *Element is an ISO 17025 accredited test lab under International Accreditation Service “TL-407”. In addition, CSA A123.21 can be found under our scope of accreditation listing.*

*This document and service are covered under Element Materials Technology Canada Inc.’s. Standard Terms and Conditions of Contract which may be found on our company’s website [www.element.com](http://www.element.com), or by calling 1-866-263-9268.*