



**COMMERCIAL**

Specify with Confidence.

# BULLETIN

Product Updates • News & Information

November 1998 REVISION:  
September 2012

## Roof Drainage

Most roofing experts agree that commercial roofs work better and last longer when they are sloped to provide drainage to the roof. This technical fact can be verified by checking various roofing contractor association technical manuals, manufacturer's specifications, and architectural literature. The advantages and reasons why roofs should be designed to drain rather than pond, include the following:

1. Water which ponds following heavy rains may lead to excessive roof loads, which can result in roof collapse. Catastrophic roof collapses can result in property destruction and injury or death to building occupants.
2. The probability of water infiltration into the roof membrane increases dramatically if water is allowed to pond on the roof. Water infiltration may occur through fishmouths, splits, cracks, poor welds, etc.
3. Historically, roofs exposed to the constant cycles of ponding and evaporation degrades at a quicker rate than roofs which provide free drainage.
4. Pondered water that enters the roofing membrane results in trapped moisture beneath the membrane layer. When heated rapidly by the sun, the resulting vapour pressure can result in roof membrane blisters.
  - a) Entrapped moisture may delaminate membrane laps due to freeze/thaw cycle.
  - b) Entrapped moisture reduces the thermal values of roof insulation.
5. Ice on ponds/puddles can loosen roof aggregate due to the physical action of the ice formation on the roof. Floating ice on a pond can also loosen aggregate/granules as the ice is blown around by wind.
6. Ponding water promotes the growth of vegetation on some membranes. Once these unintentional roof gardens flourish, plant roots and insects may affect the membrane waterproofness and durability, and objectionable odours may result.
7. Temperature differences between the ponded and the dry roof areas can cause a warping pattern of surface elongation and contraction that can wrinkle the roof membrane.
8. Lateral migration of entrapped moisture from hot to cold areas within the roof assembly can promote condensation, increasing areas of wet insulation.
9. Water often ponds near flashings, which may result in water rising above flashing waterproofing areas resulting in large roof leaks.

IKO Industries recommends that all roofs be provided with drainage. There are many definitions for drainage in the industry, and IKO uses the definition as outlined in the Canadian Roofing Contractors Association and the National Roofing Contractors Association minimum requirements. Specifically, a roof slope must be a minimum of 1:50 such that there will be no large puddles or areas of standing water within 48 hours after a heavy rainfall under conditions conducive to drying.

\*Some information based on RSI Article dated May 1998.

Thank you for considering IKO Premium Roofing and Building Envelope products. For additional information on IKO's full line of superior Commercial/Industrial Roofing, Waterproofing and Insulation products please call: **1-888-766-2468** or visit our website at **IKO.COM/COMM**.