

Document #: SDS26124

HyKote(TM) 1000 Sprayable Mastic Almond

Version number: GHS 0.0 Date of compilation: 2023-03-28

SECTION 1: Identification

1.1 Product identifier

Trade name HyKote(TM) 1000 Sprayable Mastic Almond

Alternative number(s) 10-SPMS-AL

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses Professional use

1.3 Details of the supplier of the safety data sheet

Blair Rubber Co. 5020 Enterprise Parkway Seville Ohio 44273 United States

Telephone: 1-800-321-5583 Telefax: 1-330-769-9334

e-mail: Technical@BlairRubber.com

Website: BlairRubber.com

1.4 Emergency telephone number

Emergency information service 800-424-9300 (Chemtrec); 202-483-7616 (Interna-

tional)

SECTION 2: Hazard(s) identification

2.1 Classification of the substance or mixture

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Section	Hazard class	Category	Hazard class and cat- egory	Hazard state- ment
A.6	carcinogenicity	2	Carc. 2	H351
A.8D	specific target organ toxicity - single exposure (narcotic effects, drowsiness)	3	STOT SE 3	H336
A.10	aspiration hazard	1	Asp. Tox. 1	H304
B.6	flammable liquid	3	Flam. Liq. 3	H226

For full text of abbreviations: see SECTION 16.

The most important adverse physicochemical, human health and environmental effects

The product is combustible and can be ignited by potential ignition sources.

2.2 Label elements

Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

- Signal word Danger

- Pictograms

GHS02, GHS07, GHS08



United States: en Page: 1 / 16



Document #: SDS26124

HyKote(TM) 1000 Sprayable Mastic Almond

Version number: GHS 0.0 Date of compilation: 2023-03-28

- Hazard statements

H226 Flammable liquid and vapor.

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness. H351 Suspected of causing cancer.

- Precautionary statements

P201 Obtain special instructions before use.

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.
P261 Avoid breathing dust/fume/gas/mist/vapors/spray.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/eye protection/face protection.

P301+P310 If swallowed: Immediately call a poison center/doctor.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/

shower.

P304+P340 If inhaled: Remove person to fresh air and keep comfortable for breathing.

P312 Call a poison center/doctor if you feel unwell.

P331 Do NOT induce vomiting.

P370+P378 In case of fire: Use sand, carbon dioxide or powder extinguisher to extinguish.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/container to industrial combustion plant.

- Hazardous ingredients for labelling

Parachlorobenzotrifluoride, C9-C11 Isoalkanes, Titanium dioxide

2.3 Other hazards

Hazards not otherwise classified

May be harmful in contact with skin (GHS category 5: acutely toxic - dermal).

May be harmful if inhaled (GHS category 5: acutely toxic - inhalation).

Very toxic to aquatic life with long lasting effects (GHS category 1: aquatic toxicity - acute and/or chronic).

Results of PBT and vPvB assessment

Does not contain a PBT-/vPvB-substance in a concentration of $\geq 0.1\%$.

Endocrine disrupting properties

Does not contain an endocrine disruptor (EDC) in a concentration of $\geq 0.1\%$.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not relevant (mixture)

3.2 Mixtures

United States: en Page: 2 / 16



Document #: SDS26124

HyKote(TM) 1000 Sprayable Mastic Almond

Version number: GHS 0.0 Date of compilation: 2023-03-28

Description of the mixture

Name of substance	Identifier	Wt%	Classification acc. to GHS	Pictograms
C9-C11 Isoalkanes	CAS No 68551-16-6	25 - < 50	Acute Tox. 3 / H331 STOT SE 3 / H336 Asp. Tox. 1 / H304 Flam. Liq. 3 / H226 EUH066 HNOC002 HNOC008	
Parachlorobenzotrifluoride	CAS No 98-56-6	10 - < 25	Carc. 2 / H351 Flam. Liq. 3 / H226 HNOC002 HNOC005	(3)
Calcined Clay	CAS No 92704-41-1	5 – < 10	Acute Tox. 4 / H332	(1)
Titanium dioxide	CAS No 13463-67-7	1 - < 5	Carc. 2 / H351	&

For full text of abbreviations: see SECTION 16.

SECTION 4: First-aid measures

4.1 Description of first-aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Narcotic effects.

4.3 Indication of any immediate medical attention and special treatment needed

none

United States: en Page: 3 / 16



Document #: SDS26124

HyKote(TM) 1000 Sprayable Mastic Almond

Version number: GHS 0.0 Date of compilation: 2023-03-28

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water spray, BC-powder, Carbon dioxide (CO2)

Unsuitable extinguishing media

Water jet

5.2 Special hazards arising from the substance or mixture

In case of insufficient ventilation and/or in use, may form flammable/explosive vapor-air mixture. Solvent vapors are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures.

Hazardous combustion products

Carbon monoxide (CO), Carbon dioxide (CO2)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Coordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. If substance has entered a water course or sewer, inform the responsible authority.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

United States: en Page: 4 / 16



Document #: SDS26124

HyKote(TM) 1000 Sprayable Mastic Almond

Version number: GHS 0.0 Date of compilation: 2023-03-28

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Combustible dust, may give rise to explosion hazards. Use local and general ventilation. Avoidance of ignition sources. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Use only in well-ventilated areas. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools.

- Specific notes/details

Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapors are heavier than air, spread along floors and form explosive mixtures with air. Vapors may form explosive mixtures with air.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Managing of associated risks

- Explosive atmospheres

Keep container tightly closed and in a well-ventilated place. Use local and general ventilation. Keep cool. Protect from sunlight.

- Flammability hazards

Keep away from sources of ignition - No smoking. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Protect from sunlight.

- Ventilation requirements

Use local and general ventilation. Ground/bond container and receiving equipment.

Packaging compatibilities

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

7.3 Specific end use(s)

See section 16 for a general overview.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits)											
Coun- try	Name of agent	CAS No	Identi- fier	TWA [ppm]	TWA [mg/m³]	STEL [ppm]	STEL [mg/m³]	Ceiling-C [ppm]	Ceiling-C [mg/m³]	Nota- tion	Source
US	titanium dioxide	13463-67-7	PEL		15					i, dust	29 CFR 1910.100 0
US	titanium dioxide	13463-67-7	REL							lowest, appx-A	NIOSH REL

United States: en Page: 5 / 16



Document #: SDS26124

HyKote(TM) 1000 Sprayable Mastic Almond

Version number: GHS 0.0 Date of compilation: 2023-03-28

Occupational exposure limit values (Workplace Exposure Limits)

Coun- try	Name of agent	CAS No	Identi- fier	TWA [ppm]	TWA [mg/m³]	STEL [ppm]	STEL [mg/m³]	Ceiling-C [ppm]	Ceiling-C [mg/m³]	Nota- tion	Source
US	titanium dioxide	13463-67-7	TLV®		2.5					r, fine	ACGIH® 2023
US	titanium dioxide	13463-67-7	TLV®		0.2					r, nano	ACGIH® 2023

Notation

appx-A NIOSH Potential Occupational Carcinogen (Appendix A)

Ceiling-C ceiling value is a limit value above which exposure should not occur

dust as dust fine fineparticle i inhalable fraction

lowest exposure by all routes should be carefully controlled to levels as low as possible

nano nanoparticle

r respirable fraction

STEL short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period

(unless otherwise specified)

TWA time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-

weighted average (unless otherwise specified

Relevant DNELs of components of the mixture

	'					
Name of substance	CAS No	Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
Parachlorobenzotriflu- oride	98-56-6	DNEL	0.029 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic ef- fects
Parachlorobenzotriflu- oride	98-56-6	DNEL	0.017 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic ef- fects
Parachlorobenzotriflu- oride	98-56-6	DNEL	17.6 µg/cm²	human, dermal	worker (industry)	acute - local effects
Calcined Clay	92704-41-1	DNEL	3 mg/m³	human, inhalatory	worker (industry)	chronic - systemic effects
Calcined Clay	92704-41-1	DNEL	3 mg/m³	human, inhalatory	worker (industry)	acute - systemic ef- fects
Calcined Clay	92704-41-1	DNEL	3 mg/m³	human, inhalatory	worker (industry)	chronic - local effects
Calcined Clay	92704-41-1	DNEL	3 mg/m³	human, inhalatory	worker (industry)	acute - local effects

Relevant PNECs of components of the mixture

	'					
Name of substance	CAS No	Endpoint	Threshold level	Organism	Environmental com- partment	Exposure time
Parachlorobenzotriflu- oride	98-56-6	PNEC	2 ^{µg} / _l	aquatic organisms	freshwater	short-term (single instance)
Parachlorobenzotriflu- oride	98-56-6	PNEC	0.2 ^{µg} / _l	aquatic organisms	marine water	short-term (single instance)
Parachlorobenzotriflu- oride	98-56-6	PNEC	0.032 ^{mg} / _l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)

United States: en Page: 6 / 16



Document #: SDS26124

HyKote(TM) 1000 Sprayable Mastic Almond

Version number: GHS 0.0 Date of compilation: 2023-03-28

Relevant PNECs of components of the mixture								
Name of substance	CAS No	Endpoint	Threshold level	Organism	Environmental compartment	Exposure time		
Parachlorobenzotriflu- oride	98-56-6	PNEC	0.022 ^{mg} / _{kg}	aquatic organisms	freshwater sediment	short-term (single in- stance)		
Parachlorobenzotriflu- oride	98-56-6	PNEC	0.002 ^{mg} / _{kg}	aquatic organisms	marine sediment	short-term (single in- stance)		
Parachlorobenzotriflu- oride	98-56-6	PNEC	0.026 ^{mg} / _{kg}	terrestrial organ- isms	soil	short-term (single in- stance)		
Calcined Clay	92704-41-1	PNEC	4.1 ^{mg} / _l	aquatic organisms	freshwater	short-term (single in- stance)		
Calcined Clay	92704-41-1	PNEC	0.41 ^{mg} / _l	aquatic organisms	marine water	short-term (single in- stance)		
Calcined Clay	92704-41-1	PNEC	1,400 ^{mg} / _l	aquatic organisms	sewage treatment plant (STP)	short-term (single in- stance)		

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Skin protection

- Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

United States: en Page: 7 / 16



Document #: SDS26124

HyKote(TM) 1000 Sprayable Mastic Almond

Version number: GHS 0.0 Date of compilation: 2023-03-28

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state	liquid
Color	not determined
Particle	not relevant (liquid)
Odor	characteristic

Other safety parameters

pH (value)	not determined
Melting point/freezing point	not determined
Initial boiling point and boiling range	>133.8 °C at 1 atm
Flash point	39 °C at 1 atm
Evaporation rate	not determined
Flammability (solid, gas)	not relevant, (fluid)
Vapor pressure	not determined
Density	not determined
Vapor density	this information is not available
Relative density	information on this property is not available
Solubility(ies)	not determined

Partition coefficient

- n-octanol/water (log KOW)	this information is not available
Auto-ignition temperature	>200 °C (auto-ignition temperature (liquids and gases))
Viscosity	not determined
Explosive properties	none
Oxidizing properties	none

United States: en Page: 8 / 16



Document #: SDS26124

HyKote(TM) 1000 Sprayable Mastic Almond

Version number: GHS 0.0 Date of compilation: 2023-03-28

9.2 Other information

Solvent content	88.43 %
Solid content	12.82 %
Temperature class (USA, acc. to NEC 500)	T3 (maximum permissible surface temperature on the equipment: 200°C)

SECTION 10: Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s). Risk of ignition.

If heated:

Risk of ignition

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints to prevent fire or explosion

Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

10.5 Incompatible materials

Oxidizers

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Acute toxicity

Shall not be classified as acutely toxic.

GHS of the United Nations, annex 4: May be harmful in contact with skin or if inhaled.

United States: en Page: 9 / 16



Document #: SDS26124

HyKote(TM) 1000 Sprayable Mastic Almond

Version number: GHS 0.0 Date of compilation: 2023-03-28

Acute toxicity estimate (ATE) of components of the mixture							
Name of substance CAS No Exposure route ATE							
C9-C11 Isoalkanes	68551-16-6	inhalation: vapor	>9.3 ^{mg} / _l /4h				
Calcined Clay	92704-41-1	inhalation: dust/mist	>2.07 ^{mg} / _I /4h				

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

Respiratory or skin sensitization

Shall not be classified as a respiratory or skin sensitizer.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Suspected of causing cancer.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans				
Name of substance CAS No Classification Number				
Titanium dioxide	13463-67-7	2B		
Parachlorobenzotrifluoride	98-56-6	2B		

Legend

2B Possibly carcinogenic to humans

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

May be fatal if swallowed and enters airways.

United States: en Page: 10 / 16



Document #: SDS26124

HyKote(TM) 1000 Sprayable Mastic Almond

Version number: GHS 0.0 Date of compilation: 2023-03-28

SECTION 12: Ecological information

12.1 Toxicity

Very toxic to aquatic life with long lasting effects.

Aquatic toxicity (acute) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
C9-C11 Isoalkanes	68551-16-6	LL50	>1,000 ^{mg} / _l	fish	24 h
C9-C11 Isoalkanes	68551-16-6	EL50	>1,000 ^{mg} / _l	aquatic invertebrates	24 h
C9-C11 Isoalkanes	68551-16-6	LC50	>0.004 ^{mg} / _l	aquatic invertebrates	96 h
C9-C11 Isoalkanes	68551-16-6	EC50	>0.004 ^{mg} / _l	aquatic invertebrates	48 h
Parachlorobenzotrifluor- ide	98-56-6	LC50	6.5 ^{mg} / _l	fish	24 h
Parachlorobenzotrifluor- ide	98-56-6	ErC50	>0.41 ^{mg} / _l	algae	72 h
Parachlorobenzotrifluor- ide	98-56-6	EC50	>0.41 ^{mg} /	algae	72 h
Calcined Clay	92704-41-1	LC50	>100 ^{mg} / _l	fish	96 h
Calcined Clay	92704-41-1	EC50	>100 ^{mg} / _l	aquatic invertebrates	48 h
Calcined Clay	92704-41-1	ErC50	2,500 ^{mg} / _l	algae	72 h

Aquatic toxicity (chro	onic) of compone	nts of the mixtur	e		
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
C9-C11 Isoalkanes	68551-16-6	LL50	>100 ^{mg} / _I	fish	3 h
Parachlorobenzotrifluor- ide	98-56-6	EC50	242.1 ^{mg} / _l	microorganisms	30 min
Calcined Clay	92704-41-1	EC50	2,800 ^{mg} / _l	microorganisms	16 h

12.2 Persistence and degradability

Data are not available.

12.3 Bioaccumulative potential

Data are not available.

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB. Does not contain a PBT-/vPvB-substance in a concentration of \geq 0,1%.

United States: en Page: 11 / 16



Document #: SDS26124

HyKote(TM) 1000 Sprayable Mastic Almond

Version number: GHS 0.0 Date of compilation: 2023-03-28

12.6 Endocrine disrupting properties

Does not contain an endocrine disruptor (EDC) in a concentration of $\geq 0.1\%$.

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste treatment-relevant information

Solvent reclamation/regeneration.

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packages

Only packagings which are approved (e.g. acc. to DOT) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

SECTION 14: Transport information

14.	1	UN	nun	ber

DOT	UN 1993
IMDG-Code	UN 1993
ICAO-TI	UN 1993

14.2 UN proper shipping name

DOT	Flammable liquid, n.o.s.
IMDG-Code	FLAMMABLE LIQUID, N.O.S.
ICAO-TI	Flammable liquid, n.o.s.

14.3 Transport hazard class(es)

DOT	3
IMDG-Code	3
ICAO-TI	3

14.4 Packing group

DOT	III
IMDG-Code	III
ICAO-TI	III

14.5 Environmental hazards hazardous to the aquatic environment

Environmentally hazardous substance (aquatic	C9-C11 Isoalkanes
--	-------------------

environment)

United States: en Page: 12 / 16



Document #: SDS26124

HyKote(TM) 1000 Sprayable Mastic Almond

Version number: GHS 0.0 Date of compilation: 2023-03-28

14.6 Special precautions for user

There is no additional information.

14.7 Transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

Information for each of the UN Model Regulations

Transport of dangerous goods by road or rail (49 CFR US DOT) - Additional information

Particulars in the shipper's declaration UN1993, Flammable liquid, n.o.s., 3, III, environ-

mentally hazardous

Danger label(s) 3, fish and tree





Environmental hazards yes (hazardous to the aquatic environment)

Special provisions (SP) B1, B52, IB3, T4, TP1, TP29

ERG No 128

International Maritime Dangerous Goods Code (IMDG) - Additional information

Marine pollutant Yes (hazardous to the aquatic environment) (C9-C11 Isoalkanes)

Danger label(s) 3, fish and tree





Special provisions (SP) 223, 274, 955

Excepted quantities (EQ) E1
Limited quantities (LQ) 5 L
EmS F-E, <u>S-E</u>
Stowage category A

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Environmental hazards yes (hazardous to the aquatic environment)

Danger label(s) 3



Special provisions (SP)

Excepted quantities (EQ)

Limited quantities (LQ)

A3

E1

10 L

United States: en Page: 13 / 16



Document #: SDS26124

HyKote(TM) 1000 Sprayable Mastic Almond

Version number: GHS 0.0 Date of compilation: 2023-03-28

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question National regulations (United States)

Superfund Amendment and Reauthorization Act (SARA TITLE III)

- The List of Extremely Hazardous Substances and Their Threshold Planning Quantities (EPCRA Section 302, 304)

none of the ingredients are listed

- Specific Toxic Chemical Listings (EPCRA Section 313) none of the ingredients are listed

Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA)

- List of Hazardous Substances and Reportable Quantities (CERCLA section 102a) (40 CFR 302.4) none of the ingredients are listed

Clean Air Act

none of the ingredients are listed

Right to Know Hazardous Substance List

- Hazardous Substance List (NJ-RTK)

Name of substance	CAS No	Remarks	Classifications
Titanium dioxide	13463-67-7		

California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and Toxic Enforcement Act of 1987

Proposition 65 List of chemicals			
Name acc. to inventory	CAS No	Remarks	Type of the toxicity
titanium dioxide	13463-67-7	airborne, unbound particles of respirable size	cancer
p-chloro-α,α,α-trifluorotoluene (para- Chlorobenzotrifluoride, PCBTF)	98-56-6		cancer

Industry or sector specific available guidance(s)

NPCA-HMIS® III

Hazardous Materials Identification System. American Coatings Association.

Category	Rating	Description
Chronic	*	chronic (long-term) health effects may result from repeated overexposure
Health	0	no significant risk to health
Flammability	2	material that must be moderately heated or exposed to relatively high ambient temper- atures before ignition can occur

United States: en Page: 14 / 16



Document #: SDS26124

HyKote(TM) 1000 Sprayable Mastic Almond

Version number: GHS 0.0 Date of compilation: 2023-03-28

Category	Rating	Description
Physical hazard	0	material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive
Personal protection	-	

NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

Category	Degree of hazard	Description
Flammability	2	material that must be moderately heated or exposed to relatively high ambient temper- atures before ignition can occur
Health	0	material that, under emergency conditions, would offer no hazard beyond that of ordinary combustible material
Instability	0	material that is normally stable, even under fire conditions
Special hazard		

National inventories

Country	Inventory	Status
AU	AIIC	not all ingredients are listed
CA	DSL	all ingredients are listed
CN	IECSC	all ingredients are listed
EU	ECSI	not all ingredients are listed
EU	REACH Reg.	not all ingredients are listed
JP	CSCL-ENCS	not all ingredients are listed
JP	ISHA-ENCS	not all ingredients are listed
KR	KECI	not all ingredients are listed
MX	INSQ	not all ingredients are listed
NZ	NZIoC	all ingredients are listed
PH	PICCS	not all ingredients are listed
TR	CICR	not all ingredients are listed
TW	TCSI	all ingredients are listed
US	TSCA	not all ingredients are listed

Legend

Australian Inventory of Industrial Chemicals Chemical Inventory and Control Regulation List of Existing and New Chemical Substances (CSCL-ENCS) Domestic Substances List (DSL) EC Substance Inventory (EINECS, ELINCS, NLP) AIIC CICR

CSCL-ENCS DSL

ECSI

IECSC Inventory of Existing Chemical Substances Produced or Imported in China

INSQ National Inventory of Chemical Substances

United States: en Page: 15 / 16



Document #: SDS26124

HyKote(TM) 1000 Sprayable Mastic Almond

Version number: GHS 0.0 Date of compilation: 2023-03-28

Legend

ISHA-ENCS Inventory of Existing and New Chemical Substances (ISHA-ENCS)

KECI Korea Existing Chemicals Inventory New Zealand Inventory of Chemicals NZIoC

Philippine Inventory of Chemicals and Chemical Substances (PICCS) REACH registered substances PICCS

REACH Reg. Taiwan Chemical Substance Inventory **TCSI**

TSCA **Toxic Substance Control Act**

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information, including date of preparation or last revision

Key literature references and sources for data

OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200.

Transport of dangerous goods by road or rail (49 CFR US DOT). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H226	Flammable liquid and vapor.
H304	May be fatal if swallowed and enters airways.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.

General information

PREPARED BY: Blair Rubber Research & Development Department.

WEBSITE: BlairRubber.com.

Disclaimer

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. While we have taken reasonable effort to ensure the information is correct, we give no warranty, expressed or implied, regarding its correctness. Since conditions or methods of handling and using this product are beyond our control, we do not assume responsibility and expressly disclaim liability for damages resulting from or connected with the handling, storage, use or disposal of the product.

United States: en Page: 16 / 16