



InnoviPrimeTM TPO Membrane Cleaner

Stock #: 6100022

Size: 1 U.S. gal (3.7 L)

Flash Point: 39°F (4°C)

Base: Aromatic Solvent

% Solids: 0

Packaging: Six 1-U.S. gal cans per box

Color: Clear

All reported values are nominal.

System Compatibility

InnoviPrime TPO Membrane Cleaner is intended for use with IKO InnoviTPO Roofing Systems and is approved for use with an appropriate IKO Diamond Shield Limited Warranty. Building owners, specifiers, roof consultants and roofing contractors are invited to review the IKO InnoviTPO System Specifications at www.iko.com/comm for further information on including this product as part of a complete IKO roofing system.

Used for Cleaning Dirt and Contaminants

InnoviPrime TPO Membrane Cleaner is excellent for cleaning dirt and contaminants from the field of TPO roofs and can serve as both cleaner and primer when used on cleaned TPO roofing membranes.

Key Accessory for Professional Commercial Roof Installation

InnoviPrime TPO Membrane Cleaner is a key accessory in ensuring professional TPO commercial installations.

- Used to clean TPO membrane in preparation for heat-welding or butyl adhesive-taped flashing applications.
- No special applicator required.
- VOC: 866 grams/liter — not for use in VOC regulated markets.

InnoviPrimeTM TPO Membrane Cleaner

Installation

1. Do not thin.
2. Do not allow product to puddle on the membrane for long periods.
3. Apply to an area in excess of the area to be welded using clean rags. Allow to dry thoroughly before heat welding cleaned membrane.
4. Change rags frequently. Discarded rags are a flammable hazard and should be disposed of properly.
5. Solvent resistant gloves should be worn while using this product.

Storage

1. Store in original containers only, in a dry, ventilated area.
2. Shelf Life: 12 months when properly stored.

Hazards

1. Extremely flammable. Use in well-ventilated areas, away from heat, sparks, fire, flame and ignition sources. Vapors are heavier than air and may travel a considerable distance to an ignition source and flash back.
2. No smoking when using this product.
3. Avoid repeated skin contact or the breathing of concentrated vapors. Do not inhale.

1 Gallon Freight Classification: UN1133, ADHESIVE, 3 PGII NMFC# 170060 CLASS 60

The information on this sheet is based on data supplied by the manufacturer to IKO and believed to be true and accurate. The information is offered solely for the user's consideration, investigation and verification. Nothing contained herein constitutes or represents a warranty or guarantee for which the manufacturer or the distributor can be held legally responsible.