



- NOTES:
1. REFER TO [IKO.COM/COMM](http://IKO.COM/COMM) FOR THE MOST UP TO DATE INSTALLATION INFORMATION.
  2. ANY CARPENTRY OR METAL WORK SHOULD BE DESIGNED AND CONSTRUCTED IN ACCORDANCE WITH LOCAL CODE REQUIREMENTS AND/OR PROJECT SPECIFICATIONS. THESE COMPONENTS SHOULD BE REVIEWED AND APPROVED BY A LICENSED DESIGN PROFESSIONAL. IKO ASSUMES NO RESPONSIBILITY FOR THE INSTALLATION OF THE ASSOCIATED COMPONENTS OR DAMAGE TO THE ROOF SYSTEM DUE TO FAULTY INSTALLATION.
  3. IKO ONE-PART POURABLE SEALER TO BE MOUNDED TO SHED WATER (MINIMUM DEPTH OF 2" (50 MM). IF THE SEALANT POCKET IS DEEPER THAN 2" (50 MM) IT MAY BE FILLED WITH NON-SHRINKING GROUT BEFORE APPLYING THE ONE-PART POURABLE SEALER.
  4. MEMBRANE MUST BE INSTALLED WITHIN 1/2" OF THE PENETRATION.
  5. DO NOT INSTALL OVER EXISTING SEALANT POCKETS.
  6. DO NOT USE WHEN SERVICE LINES TEMPERATURES EXCEED 160 DEGREES F (71 DEGREES C). PLEASE REFER TO DETAIL T-P-4.
  7. PREFABRICATED CORNERS MUST BE USED IF NOT A SEAM SEALED PAN.

<b>Title:</b> FIELD FABRICATED TPO COATED METAL SEALANT POCKET	<b>Detail Number:</b> <div style="text-align: right; font-size: 1.5em; font-weight: bold;">T-P-12</div>
--	--

<b>Issue Date:</b> 8/01/2025	<b>Maximum Warranty Term:</b> 30-Years	<b>Not to Scale</b>
------------------------------	--	---------------------