



**NOTES:**

1. REFER TO IKO.COM/COMM FOR THE MOST UP TO DATE INSTALLATION INFORMATION.
2. REFER TO DETAIL T-SM-1 FOR SIDE LAP POSITIONING.
3. HEAD LAPS SEAMS MUST BE A MINIMUM OF 3", REFER TO DETAIL T-SM-5.
4. JOINT COVERS ARE REQUIRED FOR 60 MIL AND 80 MIL MEMBRANES AND RECOMMENDED FOR 45 MIL MEMBRANES.
5. PRE-MOLDED JOINT COVERS ARE REQUIRED FOR ALL 25- AND 30-YEAR WARRANTIES.
6. FIELD FABRICATED JOINT COVERS ARE REQUIRED TO BE A MINIMUM OF 4" X 4" WITH ROUNDED CORNERS.
7. WHEN MEMBRANE REINFORCEMENT IS EXPOSED, REFER TO T-SM-9 FOR CUT EDGE SEALANT APPLICATION.

Title: SIDE LAP AND HEAD LAP WITH A JOINT COVER

Detail Number: **T-SM-5**

Issue Date: 8/01/2025

Maximum Warranty Term: 30-Years

Not to Scale



**COMMERCIAL**

Specify with Confidence.

