



- NOTES:
1. REFER TO IKO.COM/COMM FOR THE MOST UP TO DATE INSTALLATION INFORMATION.
 2. ANY CARPENTRY OR METAL WORK SHOULD BE DESIGNED AND CONSTRUCTED IN ACCORDANCE WITH LOCAL CODE REQUIREMENTS AND/OR PROJECT SPECIFICATIONS. THESE COMPONENTS SHOULD BE REVIEWED AND APPROVED BY A LICENSED DESIGN PROFESSIONAL. IKO ASSUMES NO RESPONSIBILITY FOR THE INSTALLATION OF THE ASSOCIATED COMPONENTS OR DAMAGE TO THE ROOF SYSTEM DUE TO FAULTY INSTALLATION.
 3. FOR PARAPET WALLS CONSTRUCTED OF STUDS, EXTENDED WIND WARRANTIES BASE TIE-INS SHALL BE INSTALLED DOWN THROUGH THE DECK, NOT INTO THE STUD WALL.
 4. PEEL STOPS CAN BE COVERED WITH THE APPROPRIATE COVER STRIP OR BE BURIED UNDER THE MEMBRANE WITH INDUCTION WELD PLATES AND FASTENERS.
 5. PEEL STOP PLATE AND FASTENER SPACING, 12" O.C. FOR WIND SPEEDS UP TO 99-MPH , AND 6" O.C. FOR WIND SPEEDS 100-MPH AND GREATER.

Title: PEEL STOP

Detail Number: T-SM-8

Issue Date: 8/01/2025

Maximum Warranty Term: 30-Years

Not to Scale



COMMERCIAL

Specify with Confidence.

