



InnoviPrime[™] TPO Membrane Cleaner (VOC Exempt)

Used for Cleaning Dirt and Contaminants

InnoviPrime TPO Membrane Cleaner (VOC Exempt) is used to remove dirt and other contaminants from TPO membranes prior to welding or to the application of flashings and tapes. InnoviPrime TPO Membrane Cleaner (VOC Exempt) is a key accessory in ensuring professional TPO commercial installations.

System Compatibility

InnoviPrime TPO Membrane Cleaner (VOC Exempt) is intended for use with InnoviTPO Roofing Systems and is approved for use with an appropriate IKO Diamond Shield Limited Warranty. Building owners, specifiers, roof consultants and roofing contractors are invited to review the IKO InnoviTPO System Specifications at www.iko.com/innovi for further information on including this product as part of a complete IKO roofing system.

Stock #: 6100018

Size: 1 U.S. Gallon (3.7 L)

Weight: 6.5 lb (2.95 kg) per U.S. Gallon

Coverage Rate: 400 ft²/Gallon (9.82 m²/L)

Packaging: Four 1-U.S. Gallon containers/box 28 boxes per pallet

Color: Clear

All reported values are nominal.

- Use prior to welding or applying butyl tape flashings.
- No special applicator required.
- VOC Exempt product.





InnoviPrime[™] TPO Membrane Cleaner (VOC Exempt)

Installation

Apply InnoviPrime TPO Membrane Cleaner (VOC Exempt) to a clean, natural fiber cloth and remove contaminants by using a scrubbing motion. InnoviPrime TPO Membrane Cleaner (VOC Exempt) is to be used only in wipe cleaning using a wetted cloth or similar material. Change cloths frequently. Allow the membrane cleaner to dry thoroughly prior to application of tape or adhesive.

Precautions

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Wear protective gloves/face protection/protective clothing/respiratory protection/protective footwear. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IN CASE OF FIRE: Use ABC powder extinguisher to put it out. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Dispose of contents and/or containers in accordance with regulations on hazardous waste or packaging and packaging waste respectively. Keep out of the reach of children.

Refer to Safety Data Sheet (SDS) prior to using InnoviPrime TPO Membrane Cleaner (VOC Exempt).

Shelf Life

12 months when stored between 60°F-80°F (16°C-27°C) in unopened containers.

Storage

Store in a dry area protected from weather and extreme temperatures. DO NOT STORE IN DIRECT SUNLIGHT.

Physical Properties and Characteristics

PROPERTY	TYPICAL VALUES
Solids:	0%
Flash Point:	0°F/4°C TTC
Solvents:	Acetone
VOC:	VOC Exempt

The information on this sheet is based on data supplied by the manufacturer to IKO and believed to be true and accurate. The information is offered solely for the user's consideration, investigation and verification. Nothing contained herein constitutes or represents a warranty or guarantee for which the manufacturer or the distributor can be held legally responsible.

