



# InnoviPrime<sup>TM</sup> TPO Pre-Wash LVOC

**Stock #:** 6100017

**Size:** 1 U.S. gal (3.7 L)

**Flash Point:** 39° F / 4° C

**Base:** Aromatic Solvent

**Coverage Rate:** 200 – 250 ft.<sup>2</sup> / gallon  
(4.9 - 6.1 m<sup>2</sup> / litre)

**% Solids:** 0

**Packaging:** Six 1-U.S Gal cans per box

**Color:** Clear

All reported values are nominal.

- Used prior to application of tape primers or seam adhesives.
- No special applicator required.
- VOC: <250 grams/liter – approved for use in VOC regulated markets.

## System Compatibility

InnoviPrime TPO Pre-Wash LVOC is intended for use with IKO InnoviTPO Roofing Systems and is approved for use with an appropriate IKO Diamond Shield Limited Warranty. Building owners, specifiers, roof consultants and roofing contractors are invited to review the IKO InnoviTPO System Specifications at [www.iko.com/innovi](http://www.iko.com/innovi) for further information on including this product as part of a complete IKO roofing system.

## Used for Cleaning Dirt and Contaminants

InnoviPrime TPO Pre-Wash LVOC is excellent for cleaning dirt and contaminants from the field of TPO roofs. When used with clean TPO roofs, InnoviPrime TPO Pre-Wash LVOC is both a cleaner and primer.

## Key Accessory for Professional Commercial Roof Installation

InnoviPrime TPO Pre-Wash LVOC is a key accessory in ensuring professional TPO commercial installations.

## InnoviPrime<sup>TM</sup> TPO Pre-Wash LVOC

### Installation

1. Do not thin.
2. This product should be scrubbed into the membrane surface thoroughly using InnoviPrime<sup>TM</sup> Scrub Pads to remove surface debris.
3. Change applicator pads frequently and cover an area in excess of the area to be seamed. No special applicator is required.
4. Solvent resistant gloves should be used when applying this product

### Storage

1. Extremely flammable.
2. Avoid repeated skin contact or the breathing of concentrated vapors.
3. Use in well ventilated areas away from heat, sparks, fire, flame and ignition sources.
4. May be stored outside if protected from water.
5. Vapors are heavier than air and may travel a considerable distance to an ignition source and flash back. Do not inhale vapors above TLV as listed on the SDS.

1 Gallon Freight Classification: UN1133, ADHESIVE, 3 PGII NMFC# 170060 CLASS 60

The information on this sheet is based on data supplied by the manufacturer to IKO and believed to be true and accurate. The information is offered solely for the user's consideration, investigation and verification. Nothing contained herein constitutes or represents a warranty or guarantee for which the manufacturer or the distributor can be held legally responsible.