



PERFORMANCE

NORDIC™ & DYNASTY® SHINGLES



Color Featured: **Castle Grey**



**HI-DEF
COLORS**



**IKO
ARMOURZONE®**



**HIGH-WIND
RESISTANCE**



**CLASS 4 IMPACT
RESISTANCE
RATING²**
(Nordic only)

For Your Customers Who Want the Best, IKO Offers Two Best-in-Class Shingles.

Nordic: Quite possibly the best laminate asphalt shingle money can buy. Offer your customers the peace of mind that comes from knowing they are providing the best for their families. As weather patterns become more unpredictable, Nordic presents your best asphalt shingle option — no matter where your customers live. Not only has this shingle earned a Class 4 impact resistance rating² but it also offers unparalleled wind uplift protection derived from IKO's exclusive ArmourZone technology.

We coat Nordic's durable fiberglass mat with a polymer-modified asphalt for heavy weight, exceptional strength and resilience, high-wind resistance and added flexibility for application in cold temperatures. This powerful combo of a durable mat and special asphalt allows IKO Nordic shingles to act as shock absorbers, to help cushion the impact of hail and earn a Class 4 impact resistance rating².

IKO's ArmourZone is the 1 1/4-inch reinforced nailing area that provides incredible fastening power and helps resist nail pull-through even in high winds of up to 130 mph (210 km/h)¹ with only four nails.

Dynasty: Wind resistance and fast installation nailed. Dynasty is an oversized, heavy-duty laminate asphalt shingle that utilizes standard oxidized asphalt instead of a polymer-modified coating. Like Nordic, Dynasty also features the ArmourZone, which offers unparalleled nail-holding power, helping the shingle resist high winds. And IKO's FastLock[®] sealant on every shingle further strengthens Dynasty's defiance of Mother Nature's wrath.

The secondary benefit of ArmourZone's larger nailing area is that it allows for easier and more accurate nailing. Combined with Dynasty's (and Nordic's) 5 7/8-inch exposure and larger-than-average overall size, it goes down faster and covers more area than most average-sized comparable laminate shingles.

Both Nordic and Dynasty are available in IKO's exclusive hi-definition color blends that will make your customer's home the envy of the neighborhood.

*This is not a guarantee of impact resistance against hail. Damage from hail is not covered under the limited warranty. Full details on reverse.



PERFORMANCE

NORDIC™ & DYNASTY® SHINGLES



SPECIFICATIONS ³	Limited Warranty ¹	Limited Lifetime	Dimensions (L x W)	40 7/8 in (1,038 mm) X 13 3/4 in (349 mm)	STANDARDS ⁴	ASTM D3462
	Iron Clad Protection ¹	15 Years	Exposure	5 7/8 in (149 mm)		ASTM D3018
	Limited Wind Warranty ¹	130 mph (210 km/h)	Coverage per Bundle	33 1/3 ft ² (3.1 m ²)		ASTM D7158 – Class H
	Blue-Green Algae Resistant ¹	Yes	Shingles per Square	60		ASTM D3161 – Class F
						ASTM E108/UL 790 – Class A
						FM 4473 – Class 4 ² (IKO Nordic shingles only)

GRANITE BLACK	GLACIER	CASTLE GREY	DRIFTSHAKE	SHADOW BROWN	SEDONA
CORNERSTONE WWD	FROSTONE GREY	BROWNSTONE	APPALACHIAN	PACIFIC RIM	BISCAYNE
ATLANTIC BLUE ⁵	MONACO RED	EMERALD GREEN	SENTINEL SLATE		

N Nordic shingles are available in color blends marked with this symbol.

D Dynasty shingles are available in color blends marked with this symbol. **Sentinel Slate is available in select markets.**

IMPORTANT! To ensure complete satisfaction, please view several full-size shingles and an actual roof installation prior to final color selection as the shingle swatches and photography shown online, in our brochures and in our **ROOFViewer**® tool may not accurately reflect shingle color and do not fully represent the entire color blend range nor the impact of sunlight.

Note: Product and color availability may vary by region. Products with Miami Dade NOA, FBC product approval and Texas Department of Insurance listings are available. Please contact IKO for details. ¹See Limited Warranty at IKO.com for complete terms, conditions, restrictions and application requirements. Shingles must be applied in accordance with application instructions and local building code requirements. ²This impact rating is solely for the purpose of enabling residential property owners to obtain a reduction in their residential insurance premium, if available. It is not to be construed as any type of express or implied warranty or guarantee of the impact performance of this shingle by the manufacturer, supplier or installer. For further detail concerning the FM 4473 standards, visit the FM Approvals website. ³All values shown are approximate. ⁴Products are developed with reference to these standards. ⁵Blue granules may fade after extensive exposure to the sun's ultraviolet rays.

The information in this literature is subject to change without notice. We assume no responsibility for errors that may appear in this literature.

Find out more about our products now by talking to an IKO sales representative or contact us directly: **In the United States, call 1-888-IKO-ROOF (1-888-456-7663). In Canada, call 1-855-IKO ROOF (1-855-456-7663).** Or visit our website at: **IKO.COM**.

