



TECHNICAL DATA SHEET



STOCK NO. 0630018

May, 2008

SBS DECKBASE 44

IKO's SBS DeckBase 44 consists of an inorganic, reinforcing mat of durable, non-woven glass fibers, heavily coated and impregnated with SBS modified asphalt. This sheet is designed for use as an economical eave protection membrane beneath asphalt shingles. SBS DeckBase 44 conforms to the CAN/CSA-A123.16 asphalt-coated glass-base sheet Type 1, and the ASTM D4601, Type 1 specification in all respects, and clause 9.26.5.2.(c) of the Building Code. IKO's roofing products are produced and designed with consideration for environmental responsibility and sustainability, incorporating quality recycled components whenever possible, manufactured in facilities that comply with the most stringent government environmental regulations, and can therefore be a part of any "green" construction project.

CHARACTERISTIC	UNITS	NOMINAL VALUE	TEST METHOD	STANDARD LIMITS
QUANTITY PER PALLET:	-	32	-	NA
PALLET SIZE:	cm (in)	132 x 112 (52 x 44)	-	-
ROLL WEIGHT:	kgs (lbs)	31 (68)	CSA A123.16	MIN: 25.4 (56)
LENGTH:	m (ft)	18 (59)	-	± 1%
WIDTH:	mm (in)	1118 (44)	-	± 3 (1/8)
AREA:	m ² (ft ²)	20 (216)	-	-
COLD FLEX:	°C (°F)	PASS	CSA A123.16	MIN: 10 (50)
TENSILE STRENGTH	MD: kN/m (lbf/in) XD: kN/m (lbf/in)	PASS PASS	CSA A123.16	MIN: 7.7 (44) MIN: 3.9 (22)

The information on this Technical Data sheet is based upon data considered to be true and accurate, based on laboratory tests and production measurements, and is offered solely for the user's consideration, investigation and verification. Nothing contained herein is representative of a warranty or guarantee for which the manufacturer can be held legally responsible. The manufacturer does not assume any responsibility for any misrepresentation or assumptions the reader may formulate.