









THE





CLASS 4 IMPACT RESISTANCE RATING<sup>3</sup>

HIGH-WIND

RESISTANCE

Homeowners in severe weather locations love Nordic Performance shingles — and so will your customers. That's because they're made with polymer-modified asphalt to cushion impact with a rubber-like effect, earning them a Class 4 impact resistance rating<sup>3</sup>. This high-performance construction makes Nordic one of the best asphalt shingles on the market.

## The IKO Difference

With a legacy of craftsmanship that spans over 75 years, we know quality. That's why contractors and their customers trust IKO to deliver beautiful, high-performing roofing systems that can withstand rigorous conditions and continue protecting families for generations to come.

## Quite possibly the best asphalt shingle on the market.

Offer your customers ultimate peace of mind with IKO's highest performing impact resistant shingle. Available in severe weather markets, Nordic shingles provide superior performance with:

- **Class 4** impact resistance rating<sup>3</sup>, the highest possible.
- Heavyweight fiberglass mat coated with a **polymer-modified asphalt** for exceptional tear-resistance and flexibility, even in cold temperatures.
- ArmourZone 1 <sup>1</sup>/<sub>4</sub>-inch reinforced woven band nailing surface for unparalleled holding power
- Stunning enhanced colour blends.
- True Square Advantage sizing providing exactly 100 square feet of coverage in every three bundles, helping minimize waste and installation costs.
- A limited **high-wind warranty**<sup>1</sup> for winds up to 210 km/h (130 mph).
- Resistance against **blue-green algae** streaks and discolouration.





## NORDIC<sup>TM</sup> Performance Shingles



SPECIFICATIONS <sup>4</sup>	Limited Warranty <sup>1</sup>	Limited Lifetime <sup>2</sup>	Dimensions (L x W)	40 7/8 in (1,038 mm) X 13 3/4 in (349 mm)	STANDARDS <sup>5</sup>	ASTM D3018
				X 13 3/4 III (343 IIIIII)		ASTM D7158 — Class H
	Iron Clad Protection <sup>1</sup>	15 Years	Exposure	5 7/8 in (149 mm)		ASTM D3161 — Class F
	Limited Wind Warranty <sup>1</sup>	210 km/h (130 mph)	Coverage per Bundle	33 1/3 sq. ft. (3.1 sq. m)		CAN/ULC S107 — Class A
			per Bullule			CSA A123.5
	Limited Algae Resistance Warranty <sup>1</sup>	10 years (blue-green)	Shingles per Square	60		FM 4473 — Class 4 <sup>3</sup>



Note: Product and colour availability may vary by region. <sup>1</sup>Refer to the Limited Warranty at IKO.com for full terms, conditions, restrictions and application requirements. Shingles must be installed per application instructions and local building codes. <sup>2</sup>"Lifetime" refers to the period from installation until the original Owner no longer owns the building. <sup>3</sup>Impact rating is solely for potential insurance premium reductions and is not a performance guarantee, implied or express warranty of any kind. Hail damage is not covered under the Limited Warranty. IKO recommends Class 4 or 3 impact resistance rated Hip and Ridge capping shingles be installed with corresponding impact rated shingles (refer to FM Approvals for more details on the FM 4473 impact resistance testing standard). <sup>4</sup>All values are approximate. <sup>5</sup>Products are developed with reference to these standards.

Become an IKO ROOFPRO Member.

Call **1-866-ROOFPRO** or visit us online **ikoroofproconnect.com** 

**IMPORTANT!** For complete satisfaction, view full-size shingles and an actual roof installation before selecting a colour. Online swatches, brochures, and our **ROOFViewer®** tool may not accurately reflect the shingle colour or full colour blend range, nor show the impact of sunlight.

Information is subject to change without notice. We assume no responsibility for errors or omissions in this literature.

Find out more about our products now by talking to an IKO sales representative or contact us directly: **1-855-IKO-ROOF (1-855-456-7663)**. Or visit our website at: **IKO.COM.** 



SEE IT ON A ROOF





► IKO.COM/NA