



PROFORMAX™

INTEGRATED ROOFING ACCESSORIES

Shingles are your home's first line of defense, but they protect, perform and look their best installed with **IKO Proformax Integrated Roofing Accessories.**



PROFORMAX ROOFING COMPONENTS

1A B C
DECK
PROTECTION

2
SYNTHETIC
UNDERLAYMENT

3
ROOF
STARTERS

4
CAPPING
SHINGLES



Meet the Complete **PROFORMAX**
Roof Building System

See reverse side for additional details. →



PROFORMAX™

INTEGRATED ROOFING ACCESSORIES

DECK PROTECTION



GoldSeam®

Use IKO GoldSeam to seal between the eave and fascia.

Size: 66.7' (20.32 m) x 4.25" (108 mm)

Box Contents: 66.7 lin ft./ roll

Units per Pallet: 150



Product dimensions shown are subject to normal manufacturing tolerances of +/- 0.5 ft. (0.15 m) on the sheet's length and +/- 1/8 in. (3 mm) on width.



GoldSeam®

Use IKO GoldSeam Tape to seal roof deck seams.

Size: 66.7' (20.32 m) x 4.25" (108 mm)

Box Contents: 66.7 lin ft./ roll

Units per Pallet: 150



Product dimensions shown are subject to normal manufacturing tolerances of +/- 0.5 ft. (0.15 m) on the sheet's length and +/- 1/8 in. (3 mm) on width.



StormShield®

A resilient ice and water protector used primarily for waterproofing purposes.

Size: 65' (19.8 m) x 36" (914 mm)

Roll Contents: 195 sq. ft. (18.1 m²)

Units per Pallet: 44



Product dimensions shown are subject to normal manufacturing tolerances of +/- 0.5 ft. (0.15 m) on the sheet's length and +/- 1/8 in. (3 mm) on width.



Stormtite®

Synthetic underlayment engineered to be used under asphalt shingles.

Size: 250 ft (76.2 m) x 48" (1,219 mm)

Roll Contents: 1000 sq ft (92.9 m²)

Units per Pallet: 56



Product dimensions shown are subject to normal manufacturing tolerances of - 0.5 to + 1 ft. (- 0.15 to + 0.30 m) on the sheet's length and +/- 1/4 in. (6.4 mm) on width.

SYNTHETIC UNDERLAYMENT

ROOF STARTERS



EdgeSeal®

Helps prevent wind uplift and blow-off in the critical areas where shingles are most vulnerable — the roof perimeter along the eaves and rakes.

Size: 67.3' (20.5 m) x 8.75" (222 mm)

Box Contents: 269.2 lin ft. (82 lin m) /4 rolls

Units per Pallet: 120 rolls (30 boxes)



Product dimensions shown are subject to normal manufacturing tolerances of +/- 0.5 ft. (0.15 m) on the sheet's length and +/- 1/8 in. (3 mm) on width.



Leading Edge Plus™

This starter course provides a guide for the first course of shingles and adds an extra layer of asphalt protection around the entire roof perimeter.

Size: 40-7/8" (1,038 mm) x 7-7/8" (200 mm)

Bundle Contents: 123 lin ft. (37 lin m)

Units per Pallet: 45



Product dimensions shown are subject to normal manufacturing tolerances of +/- 1/4 in. (6 mm) on the shingle's length and +/- 1/8 in. (3 mm) width.

CAPPING SHINGLES



UltraHP® IR^{1,2} or UltraHP®

Preformed, precut cap shingles protect and beautify. No cutting or folding.


Size: 11-1/2" (292 mm) X 10" (254 mm)

Box Contents: 20 lin ft. (6.1 lin m)

Units per Pallet: 42



Product dimensions shown are subject to normal manufacturing tolerances of +/- 1/8 in. (3 mm) on the shingle's length and width.



Hip & Ridge 12™^{1,2} or Hip & Ridge Class 4^{1,2}

Ridge cap shingles protect and beautify. Pre-tapered and perforated, no cutting required.

Size: 36" (914 mm) X 13-1/4" (337 mm)

Bundle Contents: 36.5 lin ft. (11.1 lin m)

Units per Pallet: 56



Product dimensions shown are subject to normal manufacturing tolerances of +/- 1/4 in. (6 mm) on the shingle's length and +/- 1/8 in. (3 mm) width.

Product availability and specifications may change without notice. Not all products are available in all regions. Please consult your IKO sales representative for details. All accessories are compatible with IKO shingles unless noted. ¹IKO Hip & Ridge Class 4 and UltraHP® IR have a Class 4 impact resistance rating; Hip & Ridge 12 is Class 3. IKO recommends pairing Class 4-rated hip and ridge caps with Class 4 shingles, or Class 3-rated caps with Class 3 shingles. ²Ratings are based on testing to FM 4473 (Hip & Ridge 12) and UL 2218 (UltraHP® IR). These ratings may qualify homeowners for insurance discounts, if available locally. Impact ratings do not imply any express or implied warranty or performance guarantee. For more on FM 4473 and UL 2218, visit the FM Approvals and UL Standards websites.

To find out more about the PROFORMAX accessory products or additional IKO products, please talk to an IKO sales representative, a professional roofing contractor, or contact IKO directly.
Canada 1-855-IKO-ROOF (1-855-456-7663) United States 1-888-IKO-ROOF (1-888-456-7663)
 Or visit our website at: **IKO.COM/NA**.

