




# DYNASTY® COOL COLORS PLUS

Performance Shingles | with **ArmourZone®**



## IKO Dynasty Cool Colors Plus Performance Shingles.



HIGH SOLAR  
REFLECTANCE<sup>1</sup>



TO COMPLY WITH  
CALIFORNIA TITLE 24  
COOL ROOF REQUIREMENTS<sup>2</sup>



CLASS 3 IMPACT  
RESISTANCE  
RATING<sup>7</sup>



TO COMPLY WITH  
LOS ANGELES CITY & COUNTY  
ROOF REFLECTANCE  
REQUIREMENTS<sup>2</sup>

IKO Dynasty Cool Colors Plus Performance Shingles exceed California's Title 24, Part 6 cool roof standards and can help reduce energy consumption with vibrant blends that exceed reflectivity requirements by 25%. Engineered granules limit heat transfer into attics, while the heavy-duty laminated design offers Class 3 impact resistance<sup>7</sup>. Featuring ArmourZone® technology, these shingles provide a wider nailing area, tear-resistant reinforcement, and superior protection against nail pull-through and blow-off, even in high winds.

### The IKO Difference

With a legacy of craftsmanship that spans over 75 years, we know quality. That's why contractors and their customers trust IKO to deliver beautiful, high-performing roofing systems that can withstand rigorous conditions — and continue protecting families for generations to come.

### What sets Dynasty Cool Colors Plus shingles apart:

Designed to exceed California's Title 24, Part 6 solar reflectance standards<sup>2</sup> while providing superior protection, these shingles feature:

- Solar reflectance index (SRI) of 20+<sup>2</sup> with embedded infrared-reflective pigments.
- **Class 3** impact resistance<sup>7</sup>.
- **ArmourZone®** reinforced nailing surface for exceptional holding power.
- **True Square Advantage** for precise 100 sq. ft. coverage per three bundles, reducing waste and costs.
- **FastLock®** sealant, activated by the sun to guard against wind uplift.

*Note: Available in select US markets.*





# DYNASTY® COOL COLORS PLUS

Performance Shingles | with **ArmourZone®**



<b>SPECIFICATIONS<sup>5</sup></b>	<b>Limited Warranty<sup>3</sup></b>	Limited Lifetime <sup>4</sup>	<b>Dimensions (L x W)</b>	40 7/8 in (1,038 mm) X 13 3/4 in (349 mm)	<b>STANDARDS<sup>6</sup></b>	ASTM D3462
	<b>Iron Clad Protection<sup>3</sup></b>	15 Years	<b>Exposure</b>	5 7/8 in (149 mm)		ASTM D3018
	<b>Limited Wind Warranty<sup>3</sup></b>	130 mph	<b>Coverage per Bundle</b>	33 1/3 ft <sup>2</sup> (3.1 m <sup>2</sup> )		ASTM D7158 — Class H
			<b>Shingles per Square</b>	60		ASTM D3161 — Class F
						ASTM E108/UL 790 — Class A
						CRRC-1 SRI 20+
						FM 4473 — Class 3 <sup>7</sup>



**Note:** Product and color availability may vary by region. Products with Miami Dade NOA and FBC product approval listings are available. Meets Texas Department of Insurance requirements. Contact IKO for details. <sup>3</sup>Solar reflectance is the roof's ability to reflect solar energy. SRI values range from 0 to 100 — and the higher the SRI, the better the roofing material's ability to reduce heat transfer into the home. Solar Reflectance Index (SRI) is calculated by ASTM E1980. <sup>2</sup>Shingles with an SRI of 16+ can be used to comply with California Title 24, Part 6 and shingles with an SRI of 20+ can be used to comply with LA County and City requirements, in lieu of meeting the aged solar reflectance and thermal emittance requirements. To determine if the LA City and County requirements visit the LA County website. <sup>3</sup>Refer to the Limited Warranty at IKO.com for full terms, conditions, restrictions and application requirements. Shingles must be installed per application instructions and local building codes. <sup>4</sup>"Lifetime" refers to the period from installation until the original Owner no longer owns the building. <sup>5</sup>All values are approximate. <sup>6</sup>Products are developed with reference to these standards. <sup>7</sup>Impact rating is solely for potential insurance premium reductions and is not a performance guarantee, implied or express warranty of any kind. Hail damage is not covered under the Limited Warranty. IKO recommends Class 4 or 3 impact resistance rated Hip and Ridge capping shingles be installed with corresponding impact rated shingles (refer to FM Approvals for more details on the FM 4473 impact resistance testing standard).

IKO UltraHP® high-profile hip and ridge cap shingles are available in colors that complement these Dynasty Cool Colors Plus Shingles, to protect vulnerable roof areas and to create a truly stunning roofline.

**IMPORTANT!** For complete satisfaction, view full-size shingles and an actual roof installation before selecting a color. Online swatches, brochures, and our **ROOFViewer®** tool may not accurately reflect the shingle color or full color blend range, nor show the impact of sunlight.

Information is subject to change without notice. We assume no responsibility for errors or omissions in this literature.

Find out more about our products now by talking to an IKO sales representative or contact us directly:

**1-888-IKO-ROOF (1-888-456-7663).**

Or visit our website at: **IKO.COM.**



**Become an IKO ROOFPRO Member.**

Call **1-866-ROOFPRO** or visit us online **ikoroofproconnect.com**