



DYNASTY® COOL COLORS PLUS

Performance Shingles



IKO Dynasty Cool Colors Plus Performance Shingles.



HIGH SOLAR
REFLECTANCE¹



TO COMPLY WITH
CALIFORNIA TITLE 24
COOL ROOF REQUIREMENTS²



CLASS 3 IMPACT
RESISTANCE
RATING⁷



TO COMPLY WITH
LOS ANGELES CITY & COUNTY
ROOF REFLECTANCE
REQUIREMENTS²

These shingles can be used to comply with California's Title 24, Part 6 cool roof standards, potentially helping to reduce energy consumption. Their vibrant blends exceed the minimum reflectivity requirement by 25%, and they feature specially designed granules that limit heat transmission into attics. Dynasty Cool Colors Plus are heavy-duty laminated shingles with a Class 3 impact resistance rating⁷. Featuring ArmourZone® technology, they have a wide nailing area featuring a tear resistant band for optimal nail placement and increased fastening strength, providing superior protection against nail pull-through and shingle blow-off, even in high winds.

The IKO Difference

With a legacy of craftsmanship that spans over 75 years, we know quality. That's why contractors and their customers trust IKO to deliver beautiful, high-performing roofing systems that can withstand rigorous conditions — and continue protecting families for generations to come.

What sets Dynasty Cool Colors Plus shingles apart.

Dynasty Cool Colors Plus shingles are designed to not only meet, but exceed California's Title 24, Part 6 solar reflectance requirements² — while safeguarding your home — with features like:

- A solar reflectance index (SRI) of 20 or greater² thanks to embedded infrared-reflective pigments.
- **Class 3** impact resistance rating⁷.
- **ArmourZone** 1 ¼-inch reinforced woven band nailing surface for unparalleled holding power.
- **True Square Advantage** sizing providing exactly 100 square feet of coverage in every three bundles, helping minimize waste and installation costs.
- **FastLock**® sealant, activated by the warmth of the sun to seal down and help protect against wind uplift.

Note: Available in select US markets.




DYNASTY® COOL COLORS PLUS

Performance Shingles



SPECIFICATIONS ⁵	Limited Warranty ³	Limited Lifetime ⁴	Dimensions (L x W)	40 7/8 in (1,038 mm) X 13 3/4 in (349 mm)	STANDARDS ⁶	ASTM D3462
	Iron Clad Protection ³	15 Years	Exposure	5 7/8 in (149 mm)		ASTM D3018
	Limited Wind Warranty ³	130 mph	Coverage per Bundle	33 1/3 ft ² (3.1 m ²)		ASTM D7158 — Class H
			Shingles per Square	60		ASTM D3161 — Class F
						ASTM E108/UL 790 — Class A
						CRRC-1 SRI 20+
						FM 4473 — Class 3 ⁷



Note: Product and color availability may vary by region. Products with Miami Dade NOA and FBC product approval listings are available. Meets Texas Department of Insurance requirements. Contact IKO for details. ³Solar reflectance is the roof's ability to reflect solar energy. SRI values range from 0 to 100 — and the higher the SRI, the better the roofing material's ability to reduce heat transfer into the home. Solar Reflectance Index (SRI) is calculated by ASTM E1980. ²Shingles with an SRI of 16+ can be used to comply with California Title 24, Part 6 and shingles with an SRI of 20+ can be used to comply with LA County and City requirements, in lieu of meeting the aged solar reflectance and thermal emittance requirements. To determine if the LA City and County requirements visit the LA County website. ³Refer to the Limited Warranty at IKO.com for full terms, conditions, restrictions and application requirements. Shingles must be installed per application instructions and local building codes. ⁴"Lifetime" refers to the period from installation until the original Owner no longer owns the building. ⁵All values are approximate. ⁶Products are developed with reference to these standards. ⁷Impact rating is solely for potential insurance premium reductions and is not a performance guarantee, implied or express warranty of any kind. Hail damage is not covered under the Limited Warranty. IKO recommends Class 4 or 3 impact resistance rated Hip and Ridge capping shingles be installed with corresponding impact rated shingles (refer to FM Approvals for more details on the FM 4473 impact resistance testing standard).

IKO UltraHP® high-profile hip and ridge cap shingles are available in colors that complement these Dynasty Cool Colors Plus Shingles, to protect vulnerable roof areas and to create a truly stunning roofline.

IMPORTANT! For complete satisfaction, view full-size shingles and an actual roof installation before selecting a color. Online swatches, brochures, and our **ROOFViewer®** tool may not accurately reflect the shingle color or full color blend range, nor show the impact of sunlight.

Information is subject to change without notice. We assume no responsibility for errors or omissions in this literature.



Find out more about our products now by talking to an IKO sales representative or contact us directly: **1-888-IKO-ROOF (1-888-456-7663)**. Or visit our website at: **IKO.COM**.



IKO.COM/NA

Become an **IKO ROOFPRO** Member.

Call **1-866-ROOFPRO** or visit us online ikoroofproconnect.com