

**IKO****TECHNICAL DATA SHEET**

STOCK NO. 0670088

December, 2008

No. 15 PERFORATED ASPHALT SATURATED FELT - IMPERIAL

This product consists of a resilient, high-strength cellulose fiber mat that has been saturated with premium waterproofing bitumen. Used as a vapour retarder on certain substrates or as a membrane for multi-ply built-up roofing systems, IKO's No. 15 Perforated Asphalt Saturated Felt Imperial meets or exceeds ASTM D226 Type I and CSA A123.3 Type 1 compositional and performance characteristics.

CHARACTERISTIC	UNITS	NOMINAL VALUE	TEST METHOD	STANDARD LIMITS	
QUANTITY PER PALLET:	-	25	-	N/A	
PALLET SIZE:	cm (in)	107 x 107 (42 x 42)	-	-	
LENGTH:	m (ft)	43.9 (144)	-	± 0.1%	
WIDTH:	mm (in)	914 (36)	-	± 3 (1/8)	
AREA:	m ² (ft ²)	40 (432)	-	-	
LINES:	mm (in)	51 (2) 216 (8 1/2) 286 (11 1/4) 432 (17)	-	± 6 (1/4)	
SATURATION:	%	PASS	ASTM D228	MIN: 120	
TENSILE STRENGTH	MD: XD:	kN/m (lbf/in) kN/m (lbf/in)	PASS	ASTM D146	MIN: 5.25 (30) MIN: 2.63 (15)

The information on this Technical Data sheet is based upon data considered to be true and accurate, based on laboratory tests and production measurements, and is offered solely for the user's consideration, investigation and verification. Nothing contained herein is representative of a warranty or guarantee for which the manufacturer can be held legally responsible. The manufacturer does not assume any responsibility for any misrepresentation or assumptions the reader may formulate.