



SAFETY DATA SHEET 1205

ASPHALT SATURATED ROOFING FELTS

SECTION 1 – SUBSTANCE IDENTITY AND COMPANY CONTACT INFORMATION

PRODUCT NAMES	#15 Plain Felt, #15 Lined Felt, #15 Perforated Felt, AM #15 Asphalt Felt, AM #15 Lined Felt, AM Heavy Duty Asphalt Felt, Kolamax
TRADE NAME	Asphalt Saturated Roofing Felt, Underlayment, Tar Paper
PRODUCT NUMBERS	0650034, 0650035, 0670020, 0670022, 0670088, 0670089, 0720091
CHEMICAL FAMILY	Not applicable
FORMULA	Asphalt on/in a cellulose fiber sheet
PRODUCT USE	Roofing underlayment
MANUFACTURER/SUPPLIER	IKO Industries Ltd. 71 Orenda Road Brampton, Ontario L6W 1V8
WEBSITE	www.iko.com
EMERGENCY NUMBER	CANUTEC: 1-613-996-6666 (24 hours information only)

SECTION 2 – HAZARD IDENTIFICATION

CLASSIFICATION OF THE SUBSTANCE OR MIXTURE

The products listed above are considered end-use or manufactured articles, and are not included in the scope of WHMIS 2015 or Globally Harmonization System (GHS). As such, the GHS/WHMIS labeling elements and classification are not included on this SDS.

SIGNAL WORD	Not applicable
SYMBOL(S)	Not applicable
CLASSIFICATION	Not applicable
HAZARD STATEMENTS	H335 May cause respiratory irritation
PRECAUTIONARY STATEMENTS	P201 Obtain special instructions before use P202 Do not handle until all safety precautions have been read and understood P260 Do not breathe dust/fume/gas/mist/vapours/spray. P264 Wash thoroughly after handling. P270 Do not eat, drink or smoke when using this product. P281 Use personal protective equipment as required. P308+P313 If exposed or concerned: Get medical attention. P314 Get medical advice/attention if you feel unwell. P501 Dispose of content/container in accordance with local/regional/national/international regulation.



SAFETY DATA SHEET 1205

ASPHALT SATURATED ROOFING FELTS

NFPA No information available.

HMIS No information available.

SECTION 3 – CHEMICAL COMPOSITION AND DATA ON COMPONENTS

HAZARDOUS CHEMICAL NAME	% (w/w)	CAS NUMBER
Oxidized Asphalt (Bitumen)	45 - 60	64742-93-4
Cellulose Fibre Mat	40 - 55	n/a

SECTION 4 – FIRST AID

INHALATION If affected by asphalt odor, remove victim to fresh air. Seek medical attention if symptoms persist.

INGESTION Not expected to be ingested. If ingested: rinse mouth, drink plenty of water and immediately call for medical help.

SKIN CONTACT Routine first aid treatment for cuts and abrasions from handling. Wash hands with soap and water after handling.

EYE CONTACT Flush affected eye in a stream of water for at least 15 minutes. Consult doctor if eye(s) are inflamed.

ACUTE AND CHRONIC SYMPTOMS Refer to Section 11, Toxicological Information, for additional information.

MEDICAL ATTENTION No information available.

SECTION 5 – FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA Water spray, dry chemical, or carbon dioxide.

FIRE FIGHTING No information available.

FLAMMABILITY Not flammable.

PROPERTIES:

FLASH POINT Not applicable.

FLAMMABLE LIMITS IN AIR Not applicable.

AUTO IGNITION TEMPERATURE Not applicable.



SAFETY DATA SHEET 1205

ASPHALT SATURATED ROOFING FELTS

SPECIAL PPE FOR FIRE-FIGHTERS Use NIOSH approved self-contained breathing equipment when exposed to product flames or fire, as product will emit very toxic fumes on thermal degradation.

SECTION 6 – ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS, PROTECTIVE MEASURES AND EMERGENCY PROCEDURES Ensure adequate ventilation. Use personal protective equipment described in section 8, Exposure Control and Personal Protection.

ENVIRONMENTAL PRECAUTIONS No information available.

SPILL MANAGEMENT Normal housekeeping measures. Pick up large pieces and dispose of in accordance with Local, State, Federal and Provincial regulations.

SECTION 7 - HANDLING AND STORAGE

HANDLING PROCEDURE When handling the material, wear the appropriate personal protective equipment described in section 8, Exposure Control and Personal Protection.

STORAGE PRECAUTIONS Store in a dry location protected from the elements, high temperature and flames/sparks.

OTHER PRECAUTIONS Comply with local safety standards and codes for roof work. Always use Fall Protection Systems when working on roofs. Do not walk on material that has not been securely fastened to the roof deck.

SECTION 8 – EXPOSURE CONTROL AND PERSONAL PROTECTION

CHEMICAL NAME	OCCUPATIONAL EXPOSURE LIMITS				
	ALBERTA	ONTARIO	BRITISH COLUMBIA	OSHA	ACGIH
Oxidized Asphalt (Bitumen) Fumes*	TWA : 5 mg/m ³	TWA : 0.5 mg/m ³	TWA : 0.5 mg/m ³	No information available	TWA : 0.5 mg/m ³

*Exposure is not expected under normal conditions of use.

ENGINEERING MEASURES Use local exhaust ventilation, if general ventilation is not adequate to control amount in the air.



SAFETY DATA SHEET 1205

ASPHALT SATURATED ROOFING FELTS

PERSONAL PROTECTIVE EQUIPMENT:

RESPIRATORY PROTECTION	Not required under normal conditions of use. Wear NIOSH approved respiratory protection if asphalt fume levels are above standard exposure limits.
SKIN AND BODY PROTECTION	Minimize skin contact. Protective gloves may be used when handling material.
EYE PROTECTION	Not required under normal conditions of use. Use safety glasses or goggles when necessary.
HYGIENE MEASURES	Wash hands with soap after handling.
OTHER CONTROLS	If contact is unavoidable, wear all necessary protective gear.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE (PHYSICAL STATE, COLOR etc.)	Black sheet material.
ODOR	Slight asphalt odor
ODOR THRESHOLD	No information available.
PH	No information available.
MELTING POINT/FREEZING POINT	No information available.
INITIAL BOILING POINT AND BOILING RANGE	Not applicable.
FLASH POINT	Not applicable.
EVAPORATION RATE	Not applicable.
FLAMMABILITY	Not flammable.
UPPER/LOWER FLAMMABILITY/EXPLOSIVE LIMITS	Not applicable.
VAPOR PRESSURE	Not applicable.
VAPOR DENSITY	No information available.
MOLECULAR WEIGHT	No information available.
SOLUBILITY(IES)	Insoluble.



SAFETY DATA SHEET 1205

ASPHALT SATURATED ROOFING FELTS

PARTITION COEFFICIENT: N-OCTANOL/WATER	No information available.
AUTO-IGNITION TEMPERATURE	No information available.
SPECIFIC GRAVITY	> 1.0
VISCOSITY	No information available.

SECTION 10 – STABILITY AND REACTIVITY

REACTIVITY:

CHEMICAL STABILITY	Stable at ambient temperatures.
POSSIBILITY OF HAZARDOUS REACTIONS	No information available.
CONDITIONS TO AVOID	Avoid excessive heat, sparks or flames.
INCOMPATIBLE MATERIALS	No information available.
HAZARDOUS DECOMPOSITION PRODUCTS	CO _x , SO _x , NO _x , smoke and hydrogen sulfide.

SECTION 11 – TOXICOLOGICAL INFORMATION

ACUTE/CHRONIC TOXICITY	<p>WARNING: This product may contain oxidized bitumens. The International Agency for Research on Cancer (the "IARC") published a monograph in 2013, which concluded that "occupational exposure to oxidized bitumens and their emissions during roofing operations are probably carcinogenic to humans". This warning may be updated at such time as a final determination is made and IARC has published its monograph on the matter. IARC classification: Group 2A</p> <p>The IARC found that there is "limited evidence" in humans for the carcinogenicity of occupational exposures to bitumens and bitumen emissions during roofing and mastic-asphalt work. The IARC also found that there is "sufficient evidence" in experimental animals for carcinogenicity of fume condensates generated from oxidized bitumen. All other evidence of cancer in humans and experimental animals was judged "inadequate" or "limited." The physical nature of this product may help limit any inhalation hazard from oxidized asphalt during application in its hardened state. However, physical forces such as grinding, drilling and other demolition work on this product may liberate dust containing oxidized asphalt. Burning or heating of the product may cause fumes, vapors or mists.</p>
------------------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------



SAFETY DATA SHEET 1205

ASPHALT SATURATED ROOFING FELTS

MEDICAL CONDITIONS
AGGRAVATED BY EXPOSURE No information available.

PRIMARY ROUTE OF
EXPOSURE Inhalation

HEALTH EFFECTS:

EYES None known.

SKIN None known.

INHALATION Asphalt odor may cause mild respiratory irritation, nausea, headache and/or dizziness.

INGESTION Ingestion is unlikely. If ingested, may cause irritation of the digestive tract.

STOT (SPECIFIC TARGET
ORGAN TOXICITY)-
SINGLE EXPOSURE No information available.

STOT (SPECIFIC TARGET
ORGAN TOXICITY) –
REPEATED EXPOSURE No information available.

CARCINOGENICITY Oxidized asphalt is listed as IARC Group 2A (probably carcinogenic to humans).

REPRODUCTIVE TOXICITY:

DEVELOPMENT
OF OFFSPRING No information available.

SEXUAL FUNCTION
AND FERTILITY No information available.

GERM CELL MUTAGENICITY No information available.

SECTION 12 – ECOLOGICAL INFORMATION

ECOTOXICITY No information available.

PERSISTENCE &
DEGRADABILITY No information available.

BIODEGRADATION MOBILITY No information available.

BIOACCUMULATION
POTENTIAL No information available.



SAFETY DATA SHEET 1205

ASPHALT SATURATED ROOFING FELTS

SECTION 13 – DISPOSAL CONSIDERATIONS

DISPOSAL
RECOMMENDATIONS

Follow federal, provincial/state and municipal regulations.

SECTION 14 – TRANSPORT INFORMATION

No information available.

SECTION 15 - REGULATIONS

No information available.

SECTION 16 – OTHER INFORMATION

REVISION DATE OF SDS January 23, 2018

REPLACES THE MSDS/SDS June 30, 2017
FROM

PREPARED BY HSE department

GENERAL INFORMATION 1-888-766-2468

WEBSITE www.iko.com

OTHER INFO/DISCLAIMERS Read this Safety Data Sheet before handling or disposing of this product.

This product safety information is provided to help our customers with health, safety and/or environmental matters. We have taken reasonable effort to ensure that the test methods and sources for this data are correct and reliable, however, we give no warranty, expressed or implied, regarding its correctness. Since conditions or methods of handling and using this product are beyond our control, we do not assume responsibility and expressly disclaim liability for damages resulting from or connected with the handling, storage, use or disposal of the product.

NOTE: Under government regulations, an SDS is not required for this material; it is an end use product.