

MATERIAL INFORMATION SHEET

MIS # 1207 - DRY ROOFING FELTS

IMPORTANT: Read this Material Information Sheet before handling or disposing of this product. This product safety information is provided to help our customers with health, safety and/or environmental matters. We have taken reasonable effort to ensure that the test methods and sources for this data are correct and reliable, however, we give no warranty, expressed or implied, regarding its correctness. Since conditions or methods of handling and using this product are beyond our control, we do not assume responsibility and expressly disclaim liability for damages resulting from or connected with the handling, storage, use or disposal of the product.

NOTE: Under government regulations, a MSDS is not required for this product; it is an end use product.

SECTION 1 PRODUCT AND MANUFACTURER'S INFORMATION

Manufacturer/Supplier's Name: IKO Industries Ltd.
Address: 71 Orenda Road
Brampton, Ontario
L6W 1V8
Emergency Phone: (905) 457-2880 - EXT. 3354
Product Name: Dry Roofing Felts
Chemical Name: Not applicable
Trade Name: Felt, roofing felt, flooring felt, organic felt, roofing paper, cellulosic roofing paper, dry felt, dry sheathing paper.
Chemical Family: Not applicable
Formula: A cellulose fibre sheet.

SECTION 2 PREPARATION INFORMATION

Prepared/Reviewed By: HSE Department
Phone Number: (905) 457-2880 - EXT. 3354
Date: August 3, 2015

SECTION 3 HAZARDOUS INGREDIENTS

This material contains no hazardous materials.

SECTION 4 PHYSICAL DATA

Boiling Point: Not applicable
Specific Gravity: Not applicable
Vapor Pressure: Not applicable
Evaporation Rate: Not applicable
Appearance: Solid paper, generally buff-light, or with paper dye for colouring
Odor: No odor at room temperature.

MATERIAL INFORMATION SHEET

MIS # 1207 - DRY ROOFING FELTS

SECTION 5 FIRE AND EXPLOSION DATA

<i>Flash Point:</i>	Not applicable
<i>Flammable Limits:</i>	Unknown
<i>Extinguishing Media:</i>	Dry chemical, carbon dioxide, water
<i>Special Procedures:</i>	Respirators required for fire fighting

SECTION 6 TOXICOLOGICAL PROPERTIES

<i>Exposure Limits:</i>	Not applicable
<i>Primary Route of Exposure:</i>	Not applicable
<i>Exposure Effects:</i>	Not applicable

WARNING: This product may contain oxidized bitumens. The International Agency for Research on Cancer (the "IARC") published a monograph in 2013 which concluded that "occupational exposure to oxidized bitumens and their emissions during roofing operations are probably carcinogenic to humans." The IARC found that there is "limited evidence" in humans for the carcinogenicity of occupational exposures to bitumens and bitumen emissions during roofing and mastic-asphalt work. The IARC also found that there is "sufficient evidence" in experimental animals for carcinogenicity of fume condensates generated from oxidized bitumen. All other evidence of cancer in humans and experimental animals was judged "inadequate" or "limited." The physical nature of this product may help limit any inhalation hazard from oxidized asphalt during application in its hardened state. However, physical forces such as grinding, drilling and other demolition work on this product may liberate dust containing oxidized asphalt. Burning or heating of the product may cause fumes, vapors or mists.

SECTION 7 REACTIVITY DATA

<i>Stability:</i>	Stable up to 65C (150F)
<i>Polymerization:</i>	Will not occur
<i>Materials to Avoid:</i>	Contact of acids, alkaline materials or oxidating products.
<i>Hazardous Decomposition Products:</i>	CO _x , NO _x

SECTION 8 PREVENTIVE MEASURES

<i>Spill Procedure:</i>	Not applicable
<i>Disposal Procedure:</i>	Standard waste disposal
<i>Ventilation:</i>	Not Applicable
<i>Respiratory:</i>	Dust from cellulosic fibre if inhaled may cause irritation, appropriate masks may be used if work area has excessive dust.
<i>Gloves:</i>	Not applicable
<i>Eye Protection:</i>	Not applicable
<i>Other:</i>	Not applicable

SECTION 9 FIRST AID PROCEDURES

Not applicable.